


1 LOCATION OF WATER WELL: County: Meade Fraction: NE 1/4 SE 1/4 SE 1/4 Section Number: 6 Township Number: T 32 S Range Number: R 29 EW

Distance and direction from nearest town or city street address of well if located within city?

3/4 mile S of Collins

2 WATER WELL OWNER: Denny Whiteman Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 103 Greensboro Application Number:
 City, State, ZIP Code: Plains, Kansas 67869

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 335' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 290' ft. 2. 168' ft. 3. 5-30-83 ft.
 WELL'S STATIC WATER LEVEL 168' ft. below land surface measured on mo/day/yr 5-30-83
 Pump test data: Well water was 168' ft. after 1 1/2 hours pumping 30 gpm
 Est. Yield 50 gpm: Well water was 168' ft. after 1 1/2 hours pumping 30 gpm
 Bore Hole Diameter 8 3/8 in. to 335' ft. and 335' in. to 335' ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No........; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded.....
 PVC 4 ABS 7 Fiberglass Threaded.....
 Blank casing diameter 5 in. to 275' ft., Dia. 275' in. to 275' ft., Dia. 275' in. to 275' ft.
 Casing height above land surface 12 in., weight 200 lb lbs./ft. Wall thickness or gauge No. 200 lb
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify).....
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify).....
 SCREEN-PERFORATED INTERVALS: From 275' ft. to 335' ft., From 275' ft. to 335' ft.
 GRAVEL PACK INTERVALS: From 15' ft. to 335' ft., From 15' ft. to 335' ft.

6 GROUT MATERIAL: 1 Neat cement Cement grout 3 Bentonite 4 Other.....
 Grout Intervals: From 4' ft. to 15' ft., From 15' ft. to 15' ft., From 15' ft. to 15' ft.
 What is the nearest source of possible contamination: Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? 100' South How many feet? 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	topsoil			
3	10	sand			
10	50	white clay + sand			
50	75	sand			
75	140	white clay			
140	150	sand			
150	260	white clay + sand			
260	290	blue clay			
290	335	sand + gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 7-8-83 under the business name of Bartel Dry by (signature) Robert Bartel

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 32 R 29 EW SEC. 4 NE 1/4 SE 1/4 SE 1/4