


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Meade County	Fraction 1/4 1/4 CNW 1/4	Section number 9	Township number T 32 S R	Range number 29 E/W
2. Distance and direction from nearest town or city: On Hiway 54 from the Missler Rd. 3 West, 4 to 5 tenths South 30' East			3. Owner of well: Quimby Demmitt R.R. or street: 422 N Park City, state, zip code: Meade, KS 67864		
4. Locate with "X" in section below: 			Sketch map:		
5. Type and color of material			From	To	6. Bore hole dia. 26 in. Completion date 1-29-79 Well depth 390 ft.
					7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input checked="" type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary
					8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
					9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 390 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .219
					10. Screen: Manufacturer's name Johnson Type Johnson Galv. 100-16" Slot/gauze 0-200 Plain 200-260 Perf. Set between 260-270 Screen 270-350 Perf. 350-380 Screen 380-390 Perf. ft. Gravel pack? yes Size range of material 1 to 5/8
					11. Static water level: <input type="checkbox"/> mo./day/yr. 150 ft. below land surface Date 1-15-79
					12. Pumping level below land surfaces: 162 ft. after 2 hrs. pumping 1200 g.p.m. 173 ft. after 4 hrs. pumping 2150 g.p.m. Estimated maximum yield 2150 g.p.m.
					13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____
					14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. Inches above grade
					15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
					16. Nearest source of possible contamination: ft. _____ Direction N/A Type _____ Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No
					17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Could 4 stg. 14" Bowl Model number _____ HP 200 Volts _____ Length of drop pipe 260 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)					
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling Co. 208 Business name License No. 67846 Address Box A, Garden City, KS Signed <i>[Signature]</i> Date 1-27-79 Authorized representative		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley					

3 2 2 9 9
Sec 9
1/4 C NW

December 8, 1978

Quimby Demmitt
Meade County

Location: N. W. $\frac{1}{4}$ 9-32-29 On Hiway 54 from the Missler Road
3 Miles West, 4 to 5 Tenths South, 30' East

Static Water Level -

Te. 3'

0	10	Top Soil
10	43	Brown Sandy Clay Hard
47	76	Fine to med. sand and gravel
76	140	Brown Clay
140	164	Blue Clay
164	172	Fine to med. sand and fine Gravel
172	178	Brown Clay
178	185	Fine to med. sand
185	198	Fine to med. sand and gravel
198	216	Brown Sandy Clay
216	273	Fine to med. sand and gravel
273	288	Fine to med. sand and gravel (tight)
288	380	Fine to med. sand and gravel (loose)
380	443	Brown Sandy Clay
433	476	Brown Sandy Clay mixed with White Rock
476	488	Brown Sandy Clay with Brown Rock (hard)
488	500	Red Clay Hard Pull Down

T. D. 390'