


1 LOCATION OF WATER WELL: County: Meade Fraction: NW 1/4 NW 1/4 SE 1/4 Section Number: 15 Township Number: T 32 S Range Number: R 29 EW

Distance and direction from nearest town or city street address of well if located within city?
7 West, 1/2 South, 1/2 East of Meade

2 WATER WELL OWNER: Verna Collier
 RR#, St. Address, Box #: 618 W. West Plains Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Meade, Kansas 67864 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 260 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 140 ft. 2. 240 ft. 3. .ft.
 WELL'S STATIC WATER LEVEL .ft. below land surface measured on mo/day/yr 9-5-84
 Pump test data: Well water was 145 ft. after 1 1/2 hours pumping 15 gpm
 Est. Yield 30 gpm; Well water was .ft. after .hours pumping .gpm
 Bore Hole Diameter: 8 3/8 in. to 260 .ft., and .in. to .ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped .
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded .
 PVC 4 ABS 7 Fiberglass . Threaded .
 Blank casing diameter 5 in. to 260 ft., Dia .in. to .ft., Dia .in. to .ft.
 Casing height above land surface 24 in., weight .lbs./ft. Wall thickness or gauge No. 200 16
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .
 SCREEN-PERFORATED INTERVALS: From 260 ft. to 200 ft., From .ft. to .ft.
 From .ft. to .ft., From .ft. to .ft.
 GRAVEL PACK INTERVALS: From 260 ft. to 15 ft., From .ft. to .ft.
 From .ft. to .ft., From .ft. to .ft.

6 GROUT MATERIAL: 1 Neat cement Cement grout 3 Bentonite 4 Other .
 Grout Intervals: From 15 ft. to Top ft., From .ft. to .ft., From .ft. to .ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage pond
 Direction from well? South West How many feet? 50 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Top soil			
5	100	white clay			
100	140	sand rock			
130	245	white sand			
145	240	white clay + sand rock			
240	260	sand + gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-5-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 A This Water Well Record was completed on (mo/day/yr) 9-5-84 under the business name of Beitel Dry by (signature) Libe R Beitel

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE/PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4