LOCATION OF WATER WELL: Fraction COUNTY: 088 SEWARD MM 1/A MM			Section Numb					
COUNTY: 088 SEWARD : NW 1/4 NW	1/4 NW	1/4 ;	16 	! !	T 32	S	; R 33	\$ <b>\</b>
Distance and direction from nearest town or APPROX. 13.5 MILES NORTH OF LIBERAL.			well if loca		·			
WATER WELL OWNER: SUPREME FEEDERS, RR#, St. Address, Box # : P.O. BOX 708					ulture, Div			
City, State, ZIP code : LIBERAL, KS 6	7905-		Applic	ation Nu	mber: 39722			
LOCATE WELL'S LOCATION WITH : 4 DEP AN "X" IN SECTION BOX: Dep				EVATION: 1. 12	0 2 ft. 2	2. 0	ft.	3. 0 1
\	Pump te	estdata: W	ell water was	5 241	ft. after	4 hou	ırs pu <b>a</b> p:	ing 1 <b>841</b> g
	nated Yield	1600 gpm:	Well water wa	as ()	ft. after	0 hou	ırs pump	ing 0
W    E   Bore	Hole Diamete	er	24 in. to	381 ft.	, and	in. to	0 f	t.
WELL	WATER TO BE	USED AS: 0	2 IRRIGATION					;
SW  SE	s chemical/ha	ectoriologi	ral cample co	uhaittad	to departme	ent? No :	1	
/	s, mo/day/yr	r sample wa	s submitted	upm11160	co ocpar cme	Water		infected?
-								
Blank casing diameter 16 in. to 38		in.	ELDED to 0 ft.,	, Dia		0 f		
	31 ft., Dia weight STEEL	in.	ELDED to 0 ft.,	, Dia	in. to	0 f		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 8 SCREEN OR PERFORATION OPENINGS ARE: 01 0 SCREEN PERFORATED INTERVALS: From	31 ft., Dia weight STEEL CONT. SLOT	in. 42 lbs/ 277 ft.,	to 0 ft., ft. Wall thi	, Dia ickness o	in. to r gauge No.	0 f		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C SCREEN PERFORATED INTERVALS: From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to	in. 42 lbs/ 277 ft., 328 ft.,	to 0 ft., ft. Wall thi	, Dia ickness o  ft. to ft. to	in. to r gauge No. 	0 f		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C SCREEN PERFORATED INTERVALS: From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to	in. 42 lbs/ 277 ft., 328 ft.,	ELDED to 0 ft., ft. Wall thi	, Dia ickness o  ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft.	0 f		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to	in. 42 lbs/ 277 ft., 328 ft., 381 ft.,	ELDED to 0 ft., ft. Wall thi	, Dia ickness o  ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft.	0 f		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft.	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to 0 ft. to	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall thi  From 337 f  From 0 f  From 0 f  From 0 f	, Dia ickness o ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft.	0 ft		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From From From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to 0 ft. to	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall thi  From 337 f  From 0 f  From 0 f  From 0 f	, Dia ickness o ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft		
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From From From From	31 ft., Dia weight GTEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall thi  From 337 f  From 0 f  From 0 f  From 0 f	, Dia ickness o ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From FROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contact Direction from well?  FROM : TO : LITHOLOGY O : 2 : 01 CLAY	31 ft., Dia weight GTEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From FROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contaction from well?  FROM : TO : LITHOLOGY 0 : 2 : 01 CLAY 2 : 56 : 05 SAND 11 GRAVEL	31 ft., Dia weight GTEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From FROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contact Direction from well?  FROM : TO : LITHOLOGY O : 2 : 01 CLAY	31 ft., Dia weight GTEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contact Direction from well?  FROM : TO : LITHOLOG: 0 : 2 : 01 CLAY 2 : 56 : 05 SAND 11 GRAVEL 56 : 64 : 01 CLAY	31 ft., Dia weight STEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From maination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From From From From	31 ft., Dia weight GTEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NC	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft.,	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From From From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to 0 ft. to 1., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft., 0 ft. to DNE OBSERVE	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 SCREEN OR PERFORATION OPENINGS ARE: 01 CSCREEN OR PERFORATION OPENINGS ARE: 01 CSCREEN PERFORATED INTERVALS: From From From From From From From From	31 ft., Dia weight STEEL CONT. SLOT 237 ft. to 288 ft. to 20 ft. to 0 ft. to 1., From amination: NO	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft., 0 ft. to DNE OBSERVE	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?
Blank casing diameter 16 in. to 38 Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL: 01 S SCREEN OR PERFORATION OPENINGS ARE: 01 C  SCREEN PERFORATED INTERVALS: From From GRAVEL PACK INTERVALS: From From From From From From FROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible conta Direction from well?  FROM: TO: LITHOLOGY 0: 2: 01 CLAY 2: 56: 05 SAND 11 GRAVEL 56: 64: 01 CLAY 64: 82: 05 SAND 13 FINE GRAVEL 99: 120: 05 SAND 13 FINE GRAVEL 120: 180: 05 SAND 13 FINE GRAVEL	31 ft., Dia weight STEEL CONT. SLOT  237 ft. to 288 ft. to 20 ft. to 0 ft. to t., From amination: NO  IC LOG	in. 42 lbs/ 277 ft., 328 ft., 381 ft., 0 ft., 0 ft. to DNE OBSERVE	ELDED  to 0 ft.,  ft. Wall this  From 337 from 0 fr	, Dia ickness o  ft. to ft. to ft. to ft. to	in. to r gauge No. 377 ft. 0 ft. 0 ft. 0 ft.	0 ft.	How man	y feet?

completed on (mo/day/year) 12/10/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mg/day/yr) 02/07/92 under the business name of HENKLE DRILLING & SUPPLY

COUNTY:	OF WATER WELL: 088 SEWARD	Fraction   NW 1/4 NW 1/4 NW	; Section Number 1/4 ; 16	; T 32 S	; R 33 W				
WATER WELL OWNER: SUPREME FEEDERS, INC. RR#, St. Address, Box # : P.O. BOX 708 Board of Agriculture, Division of Water Resources									
ity, Sta	ate, ZIP code	: LIBERAL, KS 67905-	Applicat	ion Number: 39722					
FROM : 240 : 277 : 284 : 320 : 330 : 335 : 354 : 7	TO : 277 : 05 S 284 : 01 C 320 : 05 S 330 : 05 S 335 : 01 C 354 : 05 S 378 : 23 S	LITHOLOGIC LOG SAND 13 FINE GRAVEL 20 LIMESTON CLAY SAND 13 FINE GRAVEL SAND 20 LIMESTONE CLAY SAND 01 CLAY SANDSTONE	1						
378	400   19 S	GHALE							
: : :	; ; ; ; ;								
! ! !	! ! !								
	:								
! ! ! !									
1 1 1 1	; ; ; ;		 						
f f l l	1 1 1 1								
; ; ; ;	1 1 5 5								
2 1 2 2 5	1 6 1 1								
1 1 1 1 1	; ; ;	· .	 						
: : :									

(signature) Douglas B. Henhle

<sup>17</sup> CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was
2 completed on (mo/day/year) 12/10/91 and this record is true to the best of my knowledge and belief. Kansas
3 Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 02/07/92
4 under the business name of HENKLE DRILLING & SUPPLY by (signature)
4