WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Stevens | Fraction: NW ¼ NW ¼ NW ¼ | Section Number: 1 | Township Number: T 32 S | Range Number: R 35 E(W)

Distance and direction from nearest town or city street address of well if located within city?
From SW corner of Moscow - 3½ Miles South, 6 Miles East, 1 Mile North, 2 Miles East — 4,930 Ft. N. 5,200 Ft. W.

2 WATER WELL OWNER: R. L. Davis
RR#, St. Address, Box # : 100 N. Jackson St.
City, State, ZIP Code : Hugoton, Kansas 67951
Board of Agriculture, Division of Water Resources Application Number: 20,225

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N / W / E / S; X in NW; 1 Mile

4 DEPTH OF COMPLETED WELL 520 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 288 ft. below land surface measured on mo/day/yr 1-24-94
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 30 in. to 520 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
(2) Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes ..... No X ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
(1) Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
2 PVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter 16 in. to 360 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. .250

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
(1) Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot (3) Mill slot (6) Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 360 ft. to 520 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 20 ft. to 520 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement (2) Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens (14) Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? North How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-21-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 2-2-94
under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller

INSTRUCTIONS: Use typewriter or ball point pen. *PLEASE PRESS FIRMLY* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R E/W SEC. ¼ ¼ ¼

The Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation and Domestic Water Systems Complete Installation and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Bob Davis
Stevens County

LOCATION: NW¼ 1-32-35 150' South of well

0'	140'	Surface and clay
140'	240'	Sand w/occ clay strip
240'	260'	Medium coarse sand w/occ brown clay streak firm to fairly loose
260'	280'	Brown clay w/occ fine to medium sand streaks and strip soft
280'	291'	Medium to coarse sand fairly loose
291'	300'	Soft brown clay w/occ fine to medium sand streak
300'	313'	Soft brown clay w/occ fine sand streak
313'	320'	Medium coarse sand w/occ clay streak
320'	340'	Medium to coarse sand w/occ dirty strip and brown clay streaks firm to fairly loose
340'	360'	Brown and light colored clay w/occ fine to medium sand streak sticky
360'	380'	Medium to coarse sand firm to fairly loose and used a trace of water
380'	400'	Medium to coarse sand and fine gravel firm to fairly loose and using a trace of water
400'	404'	Medium to coarse sand firm to fairly loose
404'	410'	Brown clay sticky
410'	420'	Medium to coarse sand firm to fairly loose
420'	440'	Medium to coarse sand and fine gravel w/occ brown clay streak firm to fairly loose and using a trace of water
440'	453'	Medium coarse sand and fine gravel firm to fairly loose and used a trace of water
453'	460'	Brown and light colored clay w/occ sandy streak
460'	468'	Clay, shale, coarse sand and sandstone conglomerated soft
468'	480'	Clay, shale, coarse sand and sandstone conglomerated tight
480'	500'	Tight conglomerate using water
500'	508'	Tight conglomerate
508'	520'	Red and yellow clay firm