


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stevens		NW 1/4 SE 1/4 NW 1/4	2	T 32 S	R 35W EW
Distance and direction from nearest town or city street address of well if located within city? Woods, KS -9miles North - 3/8 miles East - 3/8 miles South - West into location					
2 WATER WELL OWNER:		Rosel Oil Operator's / Beredco			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number: T87-487			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 440 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 298 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 298 ft. below land surface measured on mo/day/yr 11/11/87			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 8.0 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 440 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 6.625 in. to 340 ft. Dia		in. to ft. Dia in. to ft.			
Casing height above land surface 28 in. weight 3.71 lbs./ft. Wall thickness or gauge No. 280					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 340 ft. to 440 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 288 ft. From 298 ft. to 460 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 4 ft. to 10 ft. From 10 ft. to 24 ft. From 288 ft. to 298 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Dirt	.79	cu. feet of dirt	
4	10	cement grout	1.18	cu. feet of cement grout	
10	24	Bentonite grout	2.75	cu. feet of bentonite grout	
24	288	chlorinated gravel	51.82	cu. feet of chlorinated gravel	
288	298	bentonite grout	1.96	cu. feet of bentonite grout	
298	460	chlorinated gravel	31.80	cu. feet of chlorinated gravel	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/31/87 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) 12/31/87					
under the business name of Carlile Water Well Service, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					