WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

					[- 1, 1 [h]	
County 1. Location of well:	Fraction		Section	number	Township number Range number	
	NE 1/4NE 1/4 NE		13		T 39 S R 35 ₹ /W	
					ert_Larrabee Larco, Inc.	
Street address of well location if in city: MOSCOW, Kansas R.R. or street:					Liberal, Kansas 67901	
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia, 25 in. Completion date		
N					Well depth 474 ft. 7/27/76	
					7 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary	
NW NE				8. Use: Domestic Public supply Industry		
				X Irrigation Air conditioning Stock		
E SW SE				LawnOil field waterOtherOtherOther		
				Threaded Welded Surface 1211 in.		
s				RMPIbs./ft.		
5. Type and color of material From To			To	Dia.16 in. to 47.4t, depth Wall Thickness; inches or Dia in. to ft. depth gage No 219		
3. Type and color of material			From	16	10. Screen; Manufacturer's name	
Clechie and fine sand				90	Type mill-slot Dia. 16"	
					Slot/gauze 100 Length 2980	
Clay and fine sand			90	120	Set betweenft. andft.	
Clay and some fine sand			120	130		coars
200			430	150	11. Static water level: 250 t mo./day/yr.	
Med. sand and gravel					ft. below land surface Date <u>8/20/76</u>	
Course sand and gravel			150	180	12. Pumping level below land surfaces: 265 ft. after 3 hrs. pumping 1750 g.p.m.	
.i n			180	330	ft. after hrs. pumping g.p.m.	
Course pand and prayel - clay streaks			330	360	Estimated maximum yield	
Course sand and gravel - clay streaks			000	700	Yes X No Date	
fine sand, gravel, and some clay			360	390	14. Well head completion:	
Fine sand and clay streaks			3 9 0	420	Pitless adapter	
Fine sand (420–430) Med. sand and clay			1.00	1.50	With: Neat cement Bentonite Concrete] W
Fine Sand (420-450) Med. Sand and Clay			420	450	Depth: From ft. to ft.	IN
Cousse sand and blue shale layers			450	480	16. Nearest source of possible contamination: ft Direction Type	.,
Blue shale			480	510	Well disinfected upon completion? Yes No	(1)
					17. Pump: Not installed Manufacturer's nameOrthington	∞ ICC 21 ° °
					Model number <u>15M154</u> HP <u>160</u> Volts	1
			.		Length of drop pipe 4440 ft. capacity 600 g.p.m.	(≶)™
					Type: Submersible Turbine	
/II					Jet Reciprocating	راي
(Use a second sheet if needed) 18. Elevation: 19. Remarks:				Centrifugal Other 20. Water well contractor's certification:	* (V	
17. Kalidiks;				This well was drilled under my jurisdiction and this report	, 00	
Topography:				is true to the best of my knowledge and belief.	-19	
Hill					Business name Clemens Drig. 330 License No.	M
Slope					Address P. D. 199 Liberal	*FF
Valley					Signed Date 8-23	Z /M