Whi	te #1-0	C Unit #2	2 WATE	R WELL RECORD	Form WWC-	5 KSA 82	2a-1212			
	ION OF WA		Fraction	THE THEOTIE		ction Number		p Number	Range N	umber
County:	Ster	rens	NW 1/4	NW 1/4	VW 14	19		2S S	R 35W	E/W
Distance				ddress of well if local		1 1 0	Woods,	Kansas,	7 miles	North,
4 miles West, 1½ miles South, East into location										
2 WATER WELL OWNER Wilbur White  RR#, St. Address, Box #:  Mobil Oil Corp.  Board of Agriculture, Division of Water Resources										
14	e, ZIP Code	7.5	scow, Kan	sas				ation Number:	T87-31	
				OMPLETED WELL.	380	# FLEV				
AN "X"	'IN SECTIO	N BOX:	Depth(s) Ground	water Encountered	1 238	}	2	ft. 3	3	.ft.
Depth(s) Groundwater Encountered 1										
	Pump test data: Well water was ft. after hours pumping g									
Est. Yield . 1.1.0. gpm: Well water was ft. after hours pumping								imping	gpm	
Bore Hole Diameter 11. in. to								. to	ft.	
Ĭ × Į			WELL WATER T	O BE USED AS:	5 Public wa	er supply	8 Air condition	•	Injection well	1 4
llī l	SW	SE	1 Domestic				9 Dewatering		Other (Specify	l Mi
	1	1	2 Irrigation	4 Industrial			10 Observation			······· c
<u>{</u>	1		1	pacteriological sample	submitted to I					
E TYPE	OF DI ANK (	240140 11050	mitted	5 W	2.0		Vater Well Disinfo		No No Clamp	oed
_	teel	CASING USED: 3 RMP (S	2D)	5 Wrought iron 6 Asbestos-Cemen	8 Cond	rete tile ′ (specify bel			led	1. 3.
			•	7 Fiberglass		, , , , ,			aded	
Blank cas	sing diameter	4 ABS 6 625	in to 280							
Casing he	eight above la	and surface	28	ft., Dia .in., weight	3.71	lb:	s./ft. Wall thickne	ss or gauge N	o 28	0
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:	, <b>3</b>	(ZP			Asbestos-ceme		
1 S	teel	3 Stainles	ss steel	5 Fiberglass	8 R	MP (SR)	11	Other (specify)		
2 B	rass	4 Galvani	zed steel	6 Concrete tile	9 A	3S	12	None used (op	en hole)	
SCREEN	OR PERFO	RATION OPENIN	NGS ARE:	5 Gau	zed wrapped		8 Saw cut	>	11 None (ope	en hole)
1 C	ontinuous sid	t 3 N	Mill slot		e wrapped		9 Drilled hol			$\wp$
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCHEEN-PERFORATED INTERVALS. FIOIT. II. IO										
	GBAVEL BA	CK INTERVALS	From 24		228	π., Fi	rom	π. τ. τ. ι	380	π.   æ
	GHAVEL PA	CK INTERVALS	From	ft. to					0	#
6 GROUT MATERIAL: 1 Neat cement 2 Cement group 3 Bentonite 4 Other										
Grout Intervals: From 4 ft. to 10 ft., From 10 ft. to 24 ft., From 228 ft. to 238 ft.										
What is th	he nearest so	ource of possible					estock pens		bandoned wate	r well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well								> '		
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify b								elow)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									<del>Q</del>	
	from well?	South	neast	100	50014		any feet 275	. ITUO: 00	10 1 00	
FROM 0	10 A	diı	LITHOLOGIC	LOG	• 79	TO fo	et of di	LITHOLOG	ilC LOG	SEC
4	10		ment grout	•	1.18		et of ce		711+	
10	24		4 hole plu		2.75		et of gr		<i>-</i>	
24	228		lorinated		40.05		et of ch		ed grave	1 0
228	238		4 hole plu	***	1,96		et of gr			
238	380		lorinated		27.87		et of ch		ed grave	1
				_						
										× × ×
	ļ									
										≥
										<b>₩</b>
7 CONT	DACTORIC (	D I ANDOME	DIS CERTIFICATI	ON: This water we'll	woo (4) coast-	untad (0) ==	oonstructed as (	2) plugged	for my jurisdical	on and was
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Water Well Contractor's License No										
under the business name of Carlile Water Well Service, Inc. by (signature)										
INSTRU	CTIONS: Use t	pewriter or ball poi	nt pen. PLEASE PRES	SS FIRMLY and PRINT cl	early. Please fill i	blanks, under	line or circle the cor			
Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.										
i ecorus.										