


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 34 Township Number T 32 S Range Number R 36 E/W
 County: Stevens

Distance and direction from nearest town or city street address of well if located within city? 7.5 miles East of Hugoton, Ks to Moscow
black top 5 North 1 West 1.1 South and East into

2 WATER WELL OWNER: Tuls Dairy
 RR#, St. Address, Box # : Rt. 1 Box 166A Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Liberal, Ks. 67901 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 455 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 175 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 195 ft. below land surface measured on mo/day/yr 02-10-05
 Pump test data: Well water was 195 ft. after 1 hours pumping 170 gpm
 Est. Yield 170 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Dairy farm
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 8 in. to 29.5 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 24 in., weight 8.030 lbs./ft. Wall thickness or guage No. SDR 21.450
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 295 ft. to 440 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 60 ft. to 440 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 7 ft. to 450 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	27	Tan clay			
27	62	Caliche clay			
62	87	Sandy clay			
87	94	Sandstone/ sand			
94	190	Sandy clay/ clay streaks			
190	214	Fine sand			
214	290	Medium sand			
290	370	Medium sand/ clay streaks			
370	428	Fine sand/ sandy clay			
428	445	Red/tan clay/fine sand streaks			
445	455	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-10-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWWCL-430 This Water Well Record was completed on (mo/day/year) 2-10-05 under the business name of Howard Drilling Co PO Box 906 Beaver, Ok by (signature) [Signature]