

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: Stevens		SE ¼ SE ¼ SE ¼		9	T 32 S	R 36 EW
Distance and direction from nearest town or city street address of well if located within city? From Moscow , appx 3 miles South 2 1/2 West				Global Positioning System (decimal degrees, min. of 4 digits)		
				Latitude: 37.27221		
				Longitude: 101.23140		
				Elevation: 3124		
				Datum: _____		
				Data Collection Method: _____		
2 WATER WELL OWNER: Betty Lee						
RR#, St. Address, Box # : 206 S Washington						
City, State, ZIP Code : Hugoton Ks 67951						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 508 ft.				
		Depth(s) Groundwater Encountered _____ ft. _____ ft. _____ ft.				
		WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr 9/30/08				
		Pump test data: Well water was _____ ft. after 4 hours pumping _____ gpm				
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm				
		WELL WATER TO BE USED AS: 5 _____ 8 Air conditioning 11 Injection well				
		<input checked="" type="checkbox"/> Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <input type="checkbox"/> Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes _____ No <input checked="" type="checkbox"/> ; If yes, mo/day/yr Sample was submitted _____ Water Well Disinfected? Yes <input checked="" type="checkbox"/> No _____				
5 TYPE OF CASING USED:		5 Wrought Iron		8 Concrete tile		CASING JOINTS: Glued _____ Clamped <input checked="" type="checkbox"/>
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded _____
<input checked="" type="checkbox"/> PVC		4 ABS		7 Fiberglass		Threaded _____
Blank casing diameter 6 in. to 508 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft.						
Casing height above land surface 12 in., Weight 4.1 lbs./ft. Wall thickness or gauge No. 3/6						
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel		3 Stainless steel		5 Fiberglass
2 Brass		4 Galvanized steel		6 Concrete tile		8 RM (SR)
		9 ABS		11 Other (specify)		12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot		<input checked="" type="checkbox"/> Mill slot		5 Guaze wrapped
2 Louvered shutter		4 Key punched		6 Wire wrapped		7 Torch cut
						8 Saw Cut
SCREEN-PERFORATED INTERVALS:		From 3.98 ft. to 508 ft.		From _____ ft. to _____ ft.		From _____ ft. to _____ ft.
GRAVEL PACK INTERVALS:		From 25 ft. to 508 ft.		From _____ ft. to _____ ft.		From _____ ft. to _____ ft.
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		<input checked="" type="checkbox"/> Bentonite
Grout Intervals From 5 ft. to 25 ft.		From _____ ft. to _____ ft.		From _____ ft. to _____ ft.		From _____ ft. to _____ ft.
What is the nearest source of possible contamination: None observed						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage
						13 Insecticide Storage
						14 Abandoned water well
						15 Oil well/ gas well
						16 Other (specify below)
Direction from well? _____						How many feet? _____
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	Top soil				
2	120	Sandy clay				
120	134	Sand fine to med w/rock ledges				
134	187	Sandy clay				
187	218	Sand fine to med w/clay				
218	225	Sand fine to med coarse				
225	229	Sandy clay				
229	245	Sand fine to med coarse w/stringers				
245	275	Sand fine to med coarse w/clay				
275	284	Sandy clay				
284	326	Sand fine to med coarse w/clay				
326	338	Sand fine to med coarse tight				
338	454	Sand fine to med coarse w/rock				
454	508	Sand fine to med coarse				
508	520	Soap Stone				

