

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:	County <b>Stevens</b>	Fraction <b>NW 1/4 SE 1/4 SE 1/4</b>	Section number <b>35</b>	Township number <b>T 32 S</b>	Range number <b>R 37 E</b>																																							
2. Distance and direction from nearest town or city: Street address of well location if in city:	<b>2 1/2 mi. W of Hogdon, Ka</b>		3. Owner of well: R.R. or street: City, state, zip code:																																									
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile			3. Owner of well: R.R. or street: City, state, zip code:																																									
			6. Bore hole dia. <b>16</b> in. Completion date <b>12-16-78</b> Well depth <b>210</b> ft.																																									
5. Type and color of material			7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																																									
			8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:50%;"></th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> </thead> <tbody> <tr> <td>Light Gray silt</td> <td>0</td> <td>4</td> </tr> <tr> <td>dark joint clay</td> <td>4</td> <td>7</td> </tr> <tr> <td>" silt's</td> <td>7</td> <td>20</td> </tr> <tr> <td>Caliche brown w/white some sand</td> <td>20</td> <td>60</td> </tr> <tr> <td>Sand brown fine w/silt balls</td> <td>60</td> <td>88</td> </tr> <tr> <td>sand brown coarse calcified</td> <td>88</td> <td>100</td> </tr> <tr> <td>Sandy silts w/ silt rock</td> <td>100</td> <td>120</td> </tr> <tr> <td>Caliche white w/hard stringers w/sand</td> <td>120</td> <td>176</td> </tr> <tr> <td>Clay Tan</td> <td>176</td> <td>180</td> </tr> <tr> <td>silt balls &amp; silt</td> <td>180</td> <td>195</td> </tr> <tr> <td>silt balls - small tan w/sand loose</td> <td>195</td> <td>210</td> </tr> <tr> <td>Clay Tan</td> <td>210</td> <td>220</td> </tr> </tbody> </table>				From	To	Light Gray silt	0	4	dark joint clay	4	7	" silt's	7	20	Caliche brown w/white some sand	20	60	Sand brown fine w/silt balls	60	88	sand brown coarse calcified	88	100	Sandy silts w/ silt rock	100	120	Caliche white w/hard stringers w/sand	120	176	Clay Tan	176	180	silt balls & silt	180	195	silt balls - small tan w/sand loose	195	210	Clay Tan	210	220	9. Casing: <del>Material</del> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface <b>3</b> in. RMP <input type="checkbox"/> PVC <b>5640</b> Weight <b>3220</b> lbs./ft. Dia. <b>5</b> in. to <b>220</b> ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. <b>254</b>		
				From	To																																							
Light Gray silt	0	4																																										
dark joint clay	4	7																																										
" silt's	7	20																																										
Caliche brown w/white some sand	20	60																																										
Sand brown fine w/silt balls	60	88																																										
sand brown coarse calcified	88	100																																										
Sandy silts w/ silt rock	100	120																																										
Caliche white w/hard stringers w/sand	120	176																																										
Clay Tan	176	180																																										
silt balls & silt	180	195																																										
silt balls - small tan w/sand loose	195	210																																										
Clay Tan	210	220																																										
			10. Screen: Manufacturer's name <b>Slocum</b> Type <b>Saw cut</b> Dia. <b>1/8"</b> Slot/gauze <input type="checkbox"/> Length <b>40'</b> Set between <b>200'</b> ft. and <b>220'</b> ft. <b>290'</b> ft. and <b>210'</b> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material <input type="checkbox"/>																																									
			11. Static water level: <input type="checkbox"/> mo./day/yr. <b>93</b> ft. below land surface Date <b>12-16-78</b>																																									
			12. Pumping level below land surfaces: <b>96</b> ft. after <b>14</b> hrs. pumping <b>12</b> g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield <b>40</b> g.p.m.																																									
			13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date <input type="checkbox"/>																																									
			14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter <b>24"</b> inches above grade																																									
			15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <b>3</b> ft. to <b>15</b> ft.																																									
			16. Nearest source of possible contamination: ft. <b>100</b> Direction <b>NW</b> Type <b>septic</b>																																									
			Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																																									
			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name <b>Sears</b> Model number <b>?</b> HP <b>1</b> Volts <b>230</b> Length of drop pipe <b>126</b> ft. capacity <input type="checkbox"/> g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																									
			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Slocum Drilling 127</b> Business name License No. Address <b>Hogdon, Ka</b> Signed <b>Paul Slocum</b> Date <b>12-22</b> Authorized representative																																									
18. Elevation:	19. Remarks:																																											
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley																																												

78  
 32  
 37  
 33  
 NW SE SE  
 1/4 1/4 1/4