


1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 SW 1/4 Section Number 32 Township Number T 32 S Range Number R 38 EW
 County: Stevens Distance and direction from nearest town or city street address of well if located within city? From Feterita go 4 1/2 mi North 1/4 mi East into location.

2 WATER WELL OWNER: David Bozone Mobil Oil Corp.
 RR#, St. Address, Box #: HC-2 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Rolla, Kansas 67954 Application Number: T 86-431

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 400 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 245 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 155 ft. below land surface measured on mo/day/yr 1/5/87
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 100 gpm Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 11 in. to 400 ft. and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 5/8 in. to 320 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 28 in., weight 2.85 lbs./ft. Wall thickness or gauge No. .265
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 320 ft. to 400 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 220 ft. to 400 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southwest of water well How many feet? 235'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	surface			
2	43	sandy clay			
43	56	med. to large sand			
56	103	clay			
103	118	med. to large sand & gravel			
118	143	clay			
143	182	sandy clay			
182	237	clay			
237	278	60% clay & 40% fine sand			
278	303	30% clay, 20% fine sand & 50% med. to large sand			
303	316	clay			
316	400	40% clay, 35% med. to large sand & 45% gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) January 5, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) January 15, 1987 under the business name of Carlile Water Well Service, Inc. by signature

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4