			R WELL RECORD	Form WWC	C-5 KSA 82				
LOCATION OF W		Fraction	ATTY:		ection Numbe		1	Range Number	
County: Sumner		NW ¼		W 1/4	9	T 32	S	R 4 E(W)	
RR 2, Box 13, A	rgonia		ddress of well if loca	ited within cit	y? 				
WATER WELL C	WNER: Danville	Cooperative							
RR#, St. Address, B		x 67				Board of Agricult	ure, Divisi	on of Water Resources	
ity, State, ZIP Code : Danville, Kansas 67036						Application Number:			
LOCATE WELL'S WITH AN "X" IN S	SECTION BOX:							66.65	
	,,							r	
								pinggpm	
- NW	NE -							pinggpm	
w		Bore Hole Diame	ter 8 in. t	0 10	6 ft.,	and	in.	to ft.	
w x	† † † † † † † † † † † † † † † † † † †	WELL WATER T	O BE USED AS:	Public water	er supply	8 Air conditioning	<u>11 I</u>	njection well	
		1 Domestic	3 Feedlot 6	Oil field wa	ter supply	9 Dewatering		Other (Specify below)	
- SW		2 Irrigation				10 Monitoring well		Observation well	
10000		Was a chemical/ submitted	bacteriological samp	le submitted		nt? YesNo√ Vater Well Disinfected		mo/day/yr samole was No √	
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Cond	crete tile	CASING JOIN	ΓS: Glued	Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Othe	r (specify be	low)		od	
2) PVC	4 ABS		7 Fiberglass					ded. 🗸	
lank casing diamete	er . 2	. in. to . 6	ft., Dia	in.	to	ft., Dia		in. to ft.	
asing height above	land surface	-5.4 i	n., weight	<u></u>	lbs.	/ft. Wall thickness or	gauge No	sch. 40	
YPE OF SCREEN	OR PERFORATION	MATERIAL		(7)P	VC	10 Asbes	tos-ceme	nt	
1 Steel	3 Stainless	steel	5 Fiberglass	8 RI	MP (SR)	11 Other	(specify)		
2 Brass	4 Galvanize	d steel	6 Concrete tile	9 AI	BS	12 None	used (ope	en hole)	
CREEN OR PERFO	PRATION OPENING	SS ARE:	5 Gauz	ed wrapped		8 Saw cut		11 None (open hole)	
1 Continuous	slot (3)Mi	li siot	6 Wire	wrapped		9 Drilled holes			
2 Louvered sh	utter 4 Ke	y punched	7 Torc	h cut		10 Other (specify)			
CREEN-PERFORA	TED INTERVALS:	From	$.6\ldots$ ft. to $.$	16	ft., F	rom	ft.	to ft.	
		From	ft. to .		ft., F	rom	ft.	to ft.	
GRAVEL PA	ACK INTERVALS:	From	5 ft. to .	16	ft., F	rom	ft.	to ft.	
		From	ft. to .			rom	ft.	to ft.	
GROUT MATERIA			Cement grout						
Frout Intervals: Fro	<u>.0</u>	ft. to 1.	ft., From	. 1 ft.	to 5.	ft, From		. ft. to ft.	
What is the nearest :	source of possible	contamination:			10 Live	estock pens	14 At	andoned water well	
 Septic tank 	4 Latera	al lines	7 Pit privy		11 Fue	el storage	15 Oi	well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon 12 Fer			ertilizer storage (16) Other (specify below)			
3 Watertight sew	er lines 6 Seepa	age pit	9 Feedyard			ecticide storage	···Fn	nr UST basin	
Direction from well?	NE					any feet? 12			
FROM TO		LITHOLOGIC L		FROM	ТО	PLU	SGING IN	TERVALS	
0 4	Clay, silty, mo								
4 7			c, tight, Reddish					- Marwo Barr	
7 10.5	Clay, moist, pl								
10.5 12			rosity, sat., Red						
12 16	Sand (vf-c), sl.	silty, saturate	ed, mod. odor, Re	ed				· <u> </u>	
						OB3 , Tag # 0033010	, Flushm	ount	
						Project Name: Danvi	le Coop -	Argonia Excavation	
						GeoCore # 892, KDF	E # U2 0	96 10101	
CONTRACTOR'S	OR LANDOWNER'	S CERTIFICATIO	ON: This water well v	vas (1) const	ructed. (2) re	constructed, or (3) pl			
nd was completed o				\mathcal{O}^{*}				knowledge and belief.	
				nis Water We		s completed on (mo/d		8/19/05	
nder the business n			Core, Inc.		by (sign	. /1 .	Pols		
INSTRUCTIONS: 11	se typewriter or hall rais			clearly Discost			aneuron C	end top three copies to Kansas	
madination in the second secon						ne to WATER WELL OWN			