


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 1 Township Number T 32 S Range Number R 6 E/W  
 County: Harper  
 Distance and direction from nearest town or city street address of well if located within city?  
 Approx. 5 1/2 miles east of Harper, KS

2 WATER WELL OWNER: Bill Blanchat  
 RR#, St. Address, Box #: R.R. 1  
 City, State, ZIP Code: Danville, KS 67036  
 Board of Agriculture, Division of Water Resources  
 Application Number: 35,911

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 72 ft. ELEVATION: unknown  
 Depth(s) Groundwater Encountered 1. 22 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 7-5-83  
 Pump test data: Well water was NOT CK'D ft. after hours pumping gpm  
 Est. Yield 500 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 24 in. to 72 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was sub- mitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX  
 7 Fiberglass Threaded  
 Blank casing diameter 16 in. to 48 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface 12 in., weight 36.87 lbs./ft. Wall thickness or gauge No. 219  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) DOERR BRIDGE SLOT  
 SCREEN-PERFORATED INTERVALS: From 48 ft. to 72 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 72 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage FIELD  
 Direction from well? all How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	23 01	Topsoil & red clay			
23	25 17	Sand & gravel, very fine			
25	36 35	Red clay w/a few streaks of fine sand & gravel			
36	62 17	Sand & gravel, fine to very fine - clean w/a few streaks of clay & green and red shale			
62	65 01	Red clay			
65	70 17	Sand & gravel, med to fine, clean			
70	72 19	Red & green <del>shale</del>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-5-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 7-13-83 under the business name of CLARKE WELL & EQUIPMENT by (signature) *Bill Blanchat*

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
32  
R  
6  
END  
SEC 1  
SE 1/4  
SE 1/4  
SE 1/4  
SE 1/4

DP