			R WELL RECORD	Form WWC				
	OF WATER WELL:	Fraction	N. 1827		ction Numbe	· '		
County: Ha		NE 1/4		NE 1/4	12	T 32 S	R 7 EW	
103 W. 14t	irection from nearest to St., Harper				7			
2 WATER W	ELL OWNER: Kansas	s Dept. of Heal	th & Environmen	ıt				
RR#, St. Address, Box# : 1000 SW Jackson, Suite 410						Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Topeka, Kansas 66612-1367					Application Number:			
	LL'S LOCATION	4 DEPTH OF C	OMPLETED WELL	1.7	ft. ELE	VΑΤΙΟΝ:	1420.33	
WITH AN "X	"ÎN SECTION BOX:	Depth(s) Ground	dwater Encountered	1	ft	<b>. 2</b>	. ft. 3	
<b>T</b>	X	WELL'S STATIC	WATER LEVEL	6.93 ft.	below land	surface measured on mo/	day/yr4/27/2009	
1 1		Pump	test data: Well wat	erwas	<b>V.A</b> ft. a	after hour	s pumping gpn	
- N	VNE	Est. Yield . N	A gpm: Well wat	ter was	ft. a	after hour	s pumping gpm	
₩ W		Bore Hole Diam	eter <b>8</b> in. 1	to 17	ft.,	and	in. to f	
_ M	— <del> </del> =	WELL WATER	TO BE USED AS:	5 Public water	supply	8 Air conditioning	11 Injection well	
		1 Domestic	3 Feedlot	6 Oil field wate	er supply	9 Dewatering	12 Other (Specify below)	
, S	V	2 Irrigation						
<b>↓</b>		Was a chemica	l/bacteriological sam	ole submitted to			yes, mo/day/yr samble was	
<u> </u>	S	submitted			W	ater Well Disinfected? Y	es No ✓	
5 TYPE OF B	ANK CASING USED:	•	5 Wrought iron	8 Conci	rete tile	CASING JOINTS:	Glued Clamped	
1 Steel	3 RMP (S	R)	6 Asbestos-Cemen	t 9 Other	(specify bel	•,	Welded	
(2)PVC	4 ABS						Threaded. 🗸	
							in. to ff	
Casing height a	bove land surface	8.04	in., weight			/ft. Wall thickness or gau	ige No Sch. 40	
TYPE OF SCRI	EN OR PERFORATIO	ON MATERIAL		(7 <b>)</b> PV	C	10 Asbestos-	cement	
1 Steel	3 Stainles	s steel	5 Fiberglass	8 RIV	IP (SR)	11 Other (sp	ecify)	
2 Brass	4 Galvania	zed steel	6 Concrete tile	9 AB	S	12 None use	d (open hole)	
SCREEN OR P	REFORATION OPENIA	NGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)	
1 Contin	ious slot (3)	Viill slot	6 Wire	wrapped		9 Drilled holes		
2 Louver	ed shutter 4 k	Key punched	7 Torc					
SCREEN-PERF	ORATED INTERVALS						. ft. to	
							ft. to	
GRAV	EL PACK INTERVALS						. ft. to f	
		From	ft. to .			rom	. ft. to	
GROUT MAT			2 Cement grout					
Grout Intervals:	From	. ft. to 1.	ft., From	. 1 ft.	to 6.	ft, From	ft. to f	
What is the nea	rest source of possible	e contamination:			10 Live	stock pens	14 Abandoned water well	
<ol> <li>Septic tar</li> </ol>	k 4 Late	eral lines	7 Pit privy		11 Fue	storage	15 Oil well/Gas well	
						<u> </u>	16 Other (specify below)	
•		page pit	9 Feedyard			ecticide storage		
Direction from						any feet?		
	0	LITHOLOGIC	LOG	FROM	то	PLUGGI	NG INTERVALS	
	5 Concrete and							
			le, Black-Red mo	ttl	-			
		sand seams, B						
6 9		ly, silty, Lt. to						
9.5 1		<u> </u>	Brown mottled					
12 1	7 Clay, silty to	very sandy, R	ed-Brown		. ,			
						· · · · · · · · · · · · · · · · · · ·		
						MW5 , Tag # 0043765 , F	lushmount	
CONTRACTO	R'S OR I ANDOMANE	P'S CEDTIFICATI	ON: This water well y	was 11 constru	icted (2) re	constructed, or (3) plugge	ed under my jurisdiction	
				was Cipconstri			of my knowledge and belief.	
	ted on (mo/day/year)			nia Matar Mat		record is true to the best s completed om(mo/day/y	·	
	ven Contractor's Licer	15C NO	, <i>-, .,</i>	no vvaler vvel	incould was		W 1. w 41.4.44.44.77	
	see name of	· ·				// / //		
	ess name of		oCore, Inc.		by (sign	ature) Salu (C	ers. Send top three copies to Kansas	