WATER WELL R	WWC-5						
☐ Original Record ☐ Correction ☐ Chang						Well ID	
1 LOCATION OF WATER WELL:		Fraction			Township Numb	_	
County: Har	per	1/4 NEV	4NE 1/4	_3/	T 32 S	R & □ E X W	
First: Ral Street or Rural Address where well is located (if unknown, distance and							
	direction from nearest town or intersection): If at owner's address, check here:						
Address:							
City: EDmo	nd State: 0	K ZIP: 73103	Sout	12 mil	4 EMST &	South to well	
3 LOCATE WELL	4 DEPTH OF CO	MPLETED WELL:	120 ft	5 Latitude	. .	(decimal degrees)	
WITH "X" IN SECTION BOX:		Encountered: 1)		1		(decimal degrees)	
N SECTION BOX:	2) ft. 3) ft., or 4) L			Datum: WGS 84 NAD 83 NAD 27			
	WELL'S STATIC WATER LEVEL:			Source for Latitude/Longitude:			
×							
NW NE		2			(WAAS enabled? ☐ Yes ☐ No) d Survey ☐ Topographic Map		
W E		pumping gpm					
SW SE		water was					
atter nour		rs pumping	. gpm	6 Elevatio	6 Elevation:ft. Ground Level TOC		
Estimated Yield:		1.0.36 in. to 1.2.0. ft. and		Source: Land Survey GPS Topographic Map			
mile	Bote Hole Blameter.	in. to	ft.				
7 WELL WATER TO BE USED AS:							
1. Domestic:	5. 🗌 Public W	ater Supply: well ID		10. 🗌 Oil Fi	ield Water Supply: le	ease	
☐ Household				11. Test Hole: well ID			
Lawn & Garden				Cased Uncased Geotechnical			
Livestock 2. Irrigation				12. Geothermal: how many bores?			
3. Feedlot	 -			b) Open Loop Surface Discharge Inj. of Water			
4. Industrial		13. Other (specify):					
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:							
Water wall disinfested?	V CINA		•				
8 TYPE OF CASING USED: Steel X PVC Other CASING JOINTS: X Glued Clamped Welded Threaded							
8 TYPE OF CASING USED: Steel X PVC Steel X PVC Other CASING JOINTS: X Glued Clamped Welded Threaded Casing diameter for in. to fin. to							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL: □ Steel □ Steel □ Fiberglass □ PVC □ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)							
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)							
SCREEN-PERFORATED INTERVALS: From 35 ft. to 55 ft., From 95 ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft.							
GRAVEL PACK INTERVALS: From							
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From							
Nearest source of possible contamination:							
☐ Septic Tank	☐ Lateral Li			Livestock Pens	☐ Insection	eide Storage	
☐ Sewer Lines	Cess Pool	- -		Fuel Storage		oned Water Well	
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well							
Direction from well? Distance from well? 999 ft.							
10 FROM TO		OGIC LOG	FROM			PLUGGING INTERVALS	
0 2	Red TOP						
2 /20	Red Shale	· · · · · · · · · · · · · · · · · · ·					
					···		
			N				
Notes:							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)							
under my jurisdiction a	nd was completed on (mo-day-year) 7.1.1	6-15 and	this record is t	rue to the best of m	v knowledge and belief.	
Kansas Water Well Cor	ntractor's License No.	 This W	ater Well Rec	ord was comp	leted on mo-day	7-30-15	
under the business name	e of .CRoudis.	WATER WE	WSUR	OM	r (Mall)	<u> </u>	
INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of 55.00 for each constructed well atong with one white) copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone (785) 296-3565.							

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012