WATER WELL RECORD		Form W	WC-5	Di	Division of Water Resources App. No.				
1 LOCATION OF WATER WELL:		Fraction		Section	on Number	Township No.	Range Number		
County: COMANCHE			1/4 NE 1/4 SE 1/4 SE			36	T 33 S	R 20 □E 🗗 W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:									
from nearest town or intersection: If at owner's address, check here .						Latitude: (in decimal degrees)			
						Longitude: (in decimal degrees)			
					Eleva	itio <u>n:</u>	<u></u> <u></u>		
2 WATER WELL OWNER: DARREL GIRK							4, □ NAD 83, □	NAD 27	
RR#, Street Address, Box #: 1265 RD. 2						Collection Method: GPS unit (Make/Model:)			
C' Con TID C I				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
PROTECTION, KS 67127					Est. Accuracy:				
3 LOCATE WELL									
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 170 ft.								
SECT	TION BO	OX: Depth(s) Groundwater Encountered (1)							
	WELL'S STATIC WATER LEVEL30ft. below land surface measured on mo/day/yr6/19/13								
	Pump test data: Well water was. 85 ft. after 24 hours pumping. 215 gpm								
EST. YIELD 215gpm. Well water was									
W E Bore Hole Diameter 12 in. to .50 ft., and .7.7/8 in. to .170 ft.									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Output Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
✓ Irrigation									
S If yes, mo/day/yr sample was submitted									
S If yes, mo/day/yr sample was submitted									
water wen districted: Ly Tes 140									
5 TYPE OF CASING USED: Steel V PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter 8 in. to .50 ft., Diameter in. to									
Casing height above land surface. 18 in., Weight									
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☑ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREE	N-PERF	ORATED INTERVALS:							
								to ft.	
	GRAV	EL PACK INTERVALS:	From	ft. to		ft., From	ft.	to ft.	
From									
6 GRO	UT MA	TERIAL: Neat ceme	nt	✓ Benton	nite L] Other			
Grout In		From .0 ft. to			π. το	π.,	From	π. toπ.	
		est source of possible conta		I ivestock	aenc	☐ Insecticide	storage of Oth	per (specify below)	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well									
. –				Fertilizer s		Oil well/ga	1101	ΙΕ	
Direc	ction from	n well N/A		Distance	from we	ellN/A			
FROM	TO	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
0	5	TOPSOIL							
5	10	DARK CLAY							
10	15	GRAY CLAY						1,1,0,0,0	
15	20	LIGHT GRAY/TRACE OF SAND							
20	25	RED CLAY/TRACE OF SAND							
25	45	RED SHALE				-,			
45	65	RED & GRAY SHALE							
65	85	FELD SPAR							
85	120	RED CLAY & FELD SPAR							
120 130 CLAY (LOSS CIRCULATION)									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) 6/18/13									
Kansas Water Well Contractor's License No846846. This Water Well Record was completed on (mo/day/year) .6/21/13									
under the business name ofCRESCENT SERVICES.LLC by (signature)									
INSTRUC	CTIONS:	Use typewriter or ball point pen	PLEASE PRESS FIRMLY	and <u>PRINT</u> cl	early. Ple	ase fill in blanks	and check the correct	answers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Torka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html									