(>
-	Ī	٦
_	ı	7
Č	-	5
ľ	Ī	1
ç		=
ç	,	2
ľ	I	1
()
2	2	_
ſ		7

統

WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: Section Number Township Number Range Number Fraction SE 1/4 NW NW 1/4 Comanche Distance and direction from nearest town or city street address of well if located within city? 220 North Broadway, Protection, KS 2 WATER WELL OWNER: Mr. Orlin Loucks RR#, St. Address, Box # : 2932 Quivira St Board of Agriculture, Division of Water Resources Great Bend, KS 67530 Application Number: City, State, ZIP Code Depth(s) Groundwater Encountered 1.5 ft 2

WELL'S STATIC WATER 15 3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: ft. 2 _____ft. 3 ____Ft. WELL'S STATIC WATER LEVEL 18.96 ft. below land surface measured on moldaylyr 08/26/15 Pump test data: Well water was Ft. after hours pumping Gpm ΝE Est. Yield Gpm: Well water was Ft. after Hours pumping Gpm Bore Hole Diameter 8.5 In. to 32 ft. and in. to Ft.

WELL WATER TO BE USED AS: 5 Public water supply
1 Domestic 3 Feed lot 6 Oil field water supply
9 Dewatering 12 Other (Specify below) W SW. SE ._. 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ______No X ___ If yes, mo/day/yr sample was Water Well Disinfected? Yes Submitted 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 4 ABS 7 Fiberglass Threaded X Ft.. **30** Dia In. to _____ft., Dia _________ft. Blank casing diameter 2 FLUSH In., weight SCH 40 Lbs./ft. Wall thickness or gauge No. Casing height above land surface 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 11 Other (specify) 5 Fiberglass 8 RMP (SR) 1 Steel 3 Stainless steel 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 3 Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 10 Other (specify) 4 Key punched 7 Torch cut 2 Louvered shutter From 30 ft. to 32 ft. From ft. to ft. SCREEN-PERFORATED INTERVALS: SAND PACK INTERVALS: ft. to ft. to ft. From 6 GROUT MATERIAL: 3 Bentonite Neat cement 2 Cement grout 4 Other Ft. Grout Intervals From 2 0.5 ft. to 27 From 3 27 to 28 ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 12 Fertilizer storage 16 Other (specify below) 8 Sewage lagoon 9 Feedyard **Contaminated Site** 13 Insecticide storage 3 Watertight sewer lines 6 Seepage pit How many feet? Direction from well? FROM CODE LITHOLOGIC LOG FROM PLUGGING INTERVALS n 0.5 Concrete, Sand Clay 0.5 18.5 Silty Sand 18.5 19 19 25 Clay, silty End of Borehole 25 TD 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (x) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and w Completed on (mo/day/yr) 08/19/15 And this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 09/16/15 By (signature) Bradley J. Johnson Associated Environmental, Inc. under the business name of INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureauer Water Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.