BH-31	mw-3	}	WATE	R WELL RECOR	D Form V	WC-5 KSA 82a-	1212				
1 LOCATI	ON OF WAT	TER, WELL:	Fraction			Section Number		Number		ge Num	ber
County: (omar	rche_	1 NW 14		NW 14		T 3.	<u> 5</u> s	R	<u> </u>	E(W)
Distance a	and direction	from nearest tov	wn or city street a								
<u>51</u>	N Of (Christia	n Chu	rch by	Alle	4					
2 WATER	R WELL OW	NER: MO	na Aller	nder J		J					
	Address, Box		1 N Broad				Board of	of Agriculture,	Division of	Water F	lesources
City, State	, ZIP Code	~	ptection	KS 67	127		Applica	tion Number:			
LOCATI	E WELL'S L	OCATION WITH	4 DEPTH OF C	OMPLETED WEL	30	O ft. ELEVAT	TION:)A			
AN "X"	IN SECTIO	N BOX:	Depth(e) Ground	water Encountere	d 1 15	1.55 ft. 2		ft :	3		ft
Ī [78%	ZE	WELL'S STATIC Pump Est. Yield	WATER LEVEL test data: Well	18.9.0. water was	. ft. below land surf	ace measured terter	on mo/day/yr hours pu hours pu	7- <u>2</u> umping umping	9Z	gpm
≗ w b	1	F	Bore Hole Diame	eter o ir	n. to				i. to	.	ft.
₹ w h	1	,	WELL WATER 1	O BE USED AS:	5 Publi	c water supply	8 Air condition	ing 11	Injection w	ell	
7 1	1	!	1 Domestic	3 Feedlot	6 Oil fi	eld water supply	9 Dewatering	12	Other (Spe	cify bek	ow)
-	SW	SE	2 Irrigation	4 Industria	7 Lawr	and garden only	0 Monitoring	well ,			
1 1	! !					d to Department? Ye		_,	mo/day/vr	sample	was sub
<u> </u>			l .	bacteriological sail	ipio subiliillo		er Well Disinfe				
1			mitted	= 144						0 X	
_		CASING USED:		5 Wrought iron	_	Concrete tile		JOINTS: Glue		namp e d	
1 St		3 RMP (S	H)	6 Asbestos-Cen	nent 9	Other (specify below	")		ded		
2 P)	السي	4 ABS		7 Fiberglass					aded. F.1.		
Blank casi	ng diameter		- 1 - 1			.in. to					
Casing he	ight above la	and surface	<i>FWSL</i>	.in., weight	1703	lbs./f	t. Wall thickne	ss or gauge N	ю <i>, . l.</i>	54.	
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		C	7 PVC	10 /	Asbestos-ceme	ent	•	
1 Ste		3 Stainles		5 Fiberglass		8 RMP (SR)	11 (Other (specify)	١		
2 Br		4 Galvaniz		6 Concrete tile		9 ABS		None used (or			
					Causad					/anan b	- (ala)
		RATION OPENIN			Gauzed wrap	•	8 Saw cut		11 None	(open n	iole)
1 Co	ontinuous slo				Wire wrapped		9 Drilled hole				
2 Lo	uvered shutt	ter 4 K	ey punched	\sim 7	Forch cut	e Ec	10 Other (spe	ecify)			
SCREEN-	PERFORATI	ED INTERVALS:	From	5. O ft.	to	7. 5 5ft., Fron	n	ft. 1	to		ft.
			From,		to		n <i></i>				
(GRAVEL PA	CK INTERVALS:	From /.	4.0	to 29	5ft., Fron	n	ft. f	to		ft.
			From	ft.		ft., From		ft.			ft.
6 GBOLD	MATERIAL	: 1 Neat		2 Cement grout			Other				
Grout Inte					-	. ft. to					
		ource of possible				10 Liveste					
		•		7 04					bandoned,		BII
	eptic tank		ral lines	7 Pit priv		11 Fuel s			Dil well/Gas		
	wer lines	5 Cess	•	8 Sewage	e lagoon	12 Fertiliz	zer storage	16 C	Other (speci	fy below	1)
3 W	atertight sew	er lines 6 Seep	page pit	9 Feedya	ırd	13 Insect	icide storage		<i></i>		
Direction f	rom well?	South	west			How man	y feet? ~	200			
FROM	то		LITHOLOGIC	LOG	FR	OM TO		PLUGGING I	INTERVALS	3	
0.0	0.5	Fiel.	dict								
0.5	1.0	Conca	<i>it</i> ,				•	2011	Daive	r	
10	5.5	5.01	1005.	wdery		**	Hor W		11 /	27	
		Ol.	the state of	wary.					, -11-6	12,	
3.3	9.5	Hay.	Cry Masti	71	.,	1 2.42	nted	ori	1 -		
9.5	15.5	Clay, S	light by S	uty, ver	4	410	<u> </u>	- 451.6	of Fu	NU	
		plastic	<u> </u>				1104	e True		in	ces
15.5	21.0	Clay,	Slightly.	Sandy, V	ery		C KUN		1800 J	W	
		plastic	L /	, , ,	′	7,7	·	15	~		
21.0	25.5	Clay. 31	Jeditly 5	andy vie	ru	l Cl	, love	n Ta	1100		
		Martin	180-7	-, - · · · ·	7	70		100	710		
200	30.0	Picaria	11:01.+11	Sand A	2\ IL 4		~ V	541	1		
25.5	ب ب	Jan	mound.	urung as	117 41)		DM K				
		very pl	astic 1			-					
		J									
7 CONTI	RACTOR'S	OR LANDOWNE	R'S CERTIFICATI	ON: This water w	ell was (1) o	constructed, (2) recor	nstructed or (3) plugged und	der mv iuris	diction	and was
	on (mo/day	,	-29-92	Trailor W			d is true to the				
		,,		This 18/-	tor Mall De-	ord was completed o			-92°	Jellel	. ransas
		's License No	1					1 p. Z. C.	1	,	
	business na		reconnica	I Servic		by (signati		MON.	YEWY	~	
						blanks, underline or circle d one to WATER WELL OV				nsas Depa	rtment