


BH-131mw-7

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NW 1/4 Section Number 3 Township Number T 33 S Range Number R 20 EW
 County: Comanche

Distance and direction from nearest town or city street address of well if located within city?
SE corner of Broadway & 1st Alley south of Pine, Protection KS

2 WATER WELL OWNER: Mona Allender
 RR#, St. Address, Box #: 111 N Broadway
 City, State, ZIP Code: Protection KS 67127
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 25.0 ft. ELEVATION: NA
 Depth(s) Groundwater Encountered: 1. NA ft. 2. NA ft. 3. NA ft.
 WELL'S STATIC WATER LEVEL: 19.96 ft. below land surface measured on mo/day/yr 7-2-92
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm
 Est. Yield NA gpm; Well water was NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter: 8 in. to NA in. and NA in. to NA in.

WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded: Flush

Blank casing diameter: 2 in. to NA ft., Dia. 2 in. to NA ft., Dia. 2 in. to NA ft., Dia. 2 in. to NA ft.
 Casing height above land surface: Flush in., weight 1.703 lbs./ft. Wall thickness or gauge No. 154

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 10.0 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft.
 GRAVEL PACK INTERVALS: From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft., From 9.0 ft. to 24.55 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 9.0 ft. to 1.0 ft., From 9.0 ft. to 1.0 ft., From 9.0 ft. to 1.0 ft., From 9.0 ft. to 1.0 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? Southeast How many feet? 160

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	5.0	Clay, silt, slightly plastic			
5.0	10.5	Clay, plastic			
10.5	15.5	Silt, clayey slightly plastic			
15.5	17.0	Sand, very fine grained, silty			
17.0	20.5	Clay w/ some very fine silty sand streaks			
20.5	25.0	Clay w/ some very fine silty sand streaks			
Monitor Well waiver granted on 6-11-92 for KDHE Trust Fund Leaks Service by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 7-27-92
 under the business name of Geotechnical Services, Inc. by (signature) Allison Irwin

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4