

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County COMANCHE	Township name PROTECTION	Fraction NENENE	Section number 28	Town number 33	Range number 20																														
Distance and direction from nearest town or city: S-3M, W 1/2 M				3 Owner of well: H.B. BUBANK																																
Street address of well location if in city:				Address: PROTECTION KS.																																
Locate with "X" in section below: <div style="text-align: center;"> </div>				Sketch map:																																
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:50%;">2 Type and color of material</th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> </thead> <tbody> <tr> <td>BLOW SAND</td> <td>0</td> <td>12</td> </tr> <tr> <td>BLUE CLAY</td> <td>12</td> <td>18</td> </tr> <tr> <td>SAND</td> <td>18</td> <td>34</td> </tr> <tr> <td>SAND W- RED CLAY</td> <td>34</td> <td>35</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>				2 Type and color of material	From	To	BLOW SAND	0	12	BLUE CLAY	12	18	SAND	18	34	SAND W- RED CLAY	34	35																4 Well depth: 35 ft. Date of completion 11-16-74 Well diameter 9 in.		
				2 Type and color of material	From	To																														
				BLOW SAND	0	12																														
				BLUE CLAY	12	18																														
				SAND	18	34																														
				SAND W- RED CLAY	34	35																														
5 <input checked="" type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																																				
6 Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input checked="" type="checkbox"/> STOCK ONLY																																				
7 Casing: Material STEEL Sight: <u>above</u> below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 1 1/2 in. Diam. _____ Weight _____ lbs./ft. _____ 8 in. to 16 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No 5 in. to 35 ft. depth!																																				
8 Screen: J & L. Tenn and Lowell Manufacturer _____ Type STYRENE Dia. 5" Slot/gauze 5/16" GPT Length 12 ft Set between 23 ft. and 33 ft. _____ Fittings: Gravel pack <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Size range of material _____																																				
9 Static water level: 9-1/2 ft. below land surface Date 11-14-74																																				
10 Pumping level below land surfaces: _____ ft. after _____ hrs. pumping _____ g.p.m. _____ ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield _____ g.p.m.																																				
11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____																																				
12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 18" inches above grade																																				
13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> CLAY Depth: From 8 ft. to 22 ft.																																				
14 Nearest source of possible contamination: ft. 10 Direction S Type HOBBS Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																																				
15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP 3/4 Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: customer installed <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input checked="" type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																				
16 Remarks: elevation 8" iron pipe 0-16' to hold blow sand + water. 5' plastic 16" above grade to 35' ft in well? CLAY PACKED between pipe & plastic																																				
17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. WYMER BLACKSMITH & HD 228 Business name _____ License No. _____ Address PROTECTION KS Signed Wymers Date 11-16-74 Authorized representative																																				