

1 LOCATION OF WATER WELL: County: Clark Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 10 Township Number T 33 S Range Number R 24 EW Distance and direction from nearest town or city street address of well if located within city? From Ashland, Ks. - 7 miles West, 1 mile South, 1/2 mile West (on highway 160)

2 WATER WELL OWNER: Raymond McMillion Board of Agriculture, Division of Water Resources RR#, St. Address, Box #: Ashland, Kansas 67831 Application Number: City, State, ZIP Code:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram of a 2x2 section with NW, NE, SW, SE quadrants, 'X' in SE, 'N' above, 'S' below, 'W' left, 'E' right, '1 Mile' vertical scale] 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: WELL'S STATIC WATER LEVEL: 19 ft. below land surface measured on mo/day/yr 4-13-82 Pump test data: Well water was 15 gpm after 8 hours pumping Est. Yield 15 gpm Bore Hole Diameter 8 in. to 40 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below) stock well 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXXX No

5 TYPE OF CASING USED: 1 Steel, 3 RMP (SR), 2 PVC, 4 ABS, 5 Wrought iron, 8 Concrete tile, 6 Asbestos-Cement, 9 Other (specify below), 7 Fiberglass, 11 Injection well, 12 Other (Specify below) stock well CASING JOINTS: Glued XXXX, Clamped, Welded, Threaded. Blank casing diameter 5 in. to 40 ft., Dia. Casing height above land surface 12 in., weight 200 psi lbs./ft. Wall thickness or gauge No. SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 11 Other (specify), 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole) 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes, 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From GRAVEL PACK INTERVALS: From 12 ft. to 40 ft., From

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other Grout Intervals: From 0 ft. to 12 ft., From What is the nearest source of possible contamination: none, 10 Livestock pens, 14 Abandoned water well 1 Septic tank, 4 Lateral lines, 7 Pit privy, 11 Fuel storage, 15 Oil well/Gas well 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 12 Fertilizer storage, 16 Other (specify below) 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 13 Insecticide storage Direction from well? How many feet?

Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Sandy topsoil & medium sand			
15	30	Medium sand & red clay layers			
30	45	Red clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-14-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) June 23, 1983 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) Judy Crick

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 33 R 24 EW SEC. 10 SW 1/4 SW 1/4 SE 1/4

D