


NE WATER RECORD Form WWS-82a-1212

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NE 1/4 Section Number 25 Township Number T 33 S Range Number R 25 E
 County: Clark

Distance and direction from nearest town or city street address of well if located within city?
7 mi N of Englewood

2 WATER WELL OWNER: Janet Thompson Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 1015 N. Carlton Application Number:
 City, State, ZIP Code: Liberal, KS 67901

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 116 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 52 ft. 2. 678-93 ft. 3. 93 ft.
 WELL'S STATIC WATER LEVEL 52 ft. below land surface measured on mo/day/yr 6-18-93
 Pump test data: Well water was 52 ft. after 1 hours pumping 30 gpm
 Est. Yield 50 gpm; Well water was 52 ft. after 1 hours pumping 30 gpm
 Bore Hole Diameter: 8 3/4 in. to 120 ft., and 120 in. to 120 ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes ✓ No ✓

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ✓
 7 Fiberglass Threaded ✓
 Blank casing diameter 5 in. to 76 ft., Dia 5 in. to 76 ft., Dia 5 in. to 76 ft.
 Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 200.16
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ✓
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ✓
 SCREEN-PERFORATED INTERVALS: From 76 ft. to 116 ft., From 76 ft. to 116 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 110 ft., From 20 ft. to 110 ft.

6 GROUT MATERIAL: 1 Neat cement Cement grout 3 Bentonite 4 Other ✓
 Grout Intervals: From 20 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	sandy topsoil			
5	18	brown clay			
18	25	sand			
25	32	brown clay			
32	40	sand + gravel			
40	48	brown clay			
48	55	sand + gravel			
55	62	brown clay			
62	65	sand + gravel			
65	70	brown clay			
70	116	sand + gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 6-18-93 under the business name of Bartel Well Drilling, Inc by (signature) Reuben J. Bartel

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EAW
SEC.
1/4
1/4
1/4