


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SE 1/4 Section Number 25 Township Number T 33 S Range Number R 26 E 10
 County: Meade
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Cimarron Grazing Assn.
 RR#, St. Address, Box #: % Jim Bisel Ashland, KS 67831
 City, State, ZIP Code: % Jim Bisel Ashland, KS 67831
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 150 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 71 ft. 2. 124 ft. 3. 124 ft.
 WELL'S STATIC WATER LEVEL 64 ft. below land surface measured on mo/day/yr 5-5-94
 Pump test data: Well water was 125 ft. after 2 hours pumping 3.5 gpm
 Est. Yield 4 gpm: Well water was 125 ft. after 2 hours pumping 3.5 gpm
 Bore Hole Diameter 9 in. to 150 ft., and 150 in. to 150 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well ☒ 12 Other (Specify below) Windmill for livestock
 Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☐ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
☒ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass
 Blank casing diameter 5 in. to 8.70 ft. Dia 5 in. to 9.0-120 ft. Dia 5 in. to 9.0-120 ft. Dia
 Casing height above land surface 1 in., weight 2.87 lbs./ft. Wall thickness or gauge No. SDR21
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 90 ft., From 120 ft. to 150 ft., From 150 ft. to 100 ft., From 90 ft. to 20 ft.
 GRAVEL PACK INTERVALS: From 70 ft. to 90 ft., From 120 ft. to 150 ft., From 150 ft. to 100 ft., From 90 ft. to 20 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From 90 ft. to 100 ft., From 100 ft. to 100 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☒ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? West
 How many feet? 1/2 mi

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	12	clay - Dark Brown			
12	28	clay - light Brown			
28	30	course rock			
30	71	clay - red, some white material (occasional)			
71	85	clay - red fine sand (limestone)			
85	96	clay - red			
96	120	clay - red, some white as well			
120	140	clay - red, some fine sand			
140	150	clay - red some white as well			
150		very hard red & white			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-5-94 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 572 This Water Well Record was completed on (mo/day/yr) 5-18-94
 under the business name of Ashland Well Service by (signature) Don Biesel