

KSA 82a-1212

LOCATION OF WATER WELL: meade, KS. 8 South - 4 East & 1/2 South & East into
COUNTY: meade FRACTION: SW 1/4 SW 1/4 NW 1/4 SECTION NUMBER: 21 TOWNSHIP NUMBER: 33 S RANGE NUMBER: 27 E
DISTANCE AND DIRECTION FROM NEAREST TOWN OR CITY STREET ADDRESS OF WELL IF LOCATED WITHIN CITY?
WATER WELL OWNER: John Dye
R#, ST. ADDRESS, BOX # BOX 504
CITY, STATE, ZIP CODE meade, KS. 67864
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
DEPTH OF COMPLETED WELL: 340 ft. ELEVATION:
WELL'S STATIC WATER LEVEL: 168 ft. below land surface measured on mo/day/yr 4-3-98
PUMP TEST DATA: Well water was ft. after hours pumping
EST. YIELD gpm Well water was ft. after hours pumping
BORE HOLE DIAMETER: 12 1/4 in. to 20 ft. and 9 1/4 in. to 340
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter: 5.56 in. to ft., Dia. in. to ft., Dia. in. to
Casing height above land surface: 30 in., weight: 200 psi lbs./ft. Wall thickness or gauge No. SDR-21
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot #035 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 260 ft. to 340 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 190 ft. to 340 ft. From ft. to ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout intervals: From 5 ft. to 25 ft. From 185 ft. to 190 ft. From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? North How many feet? 125
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 4 Topsoil 304 312 Redbed
4 48 Tan Sandy Clay & Caliche 312 315 Red Sand
48 58 Pink Sand 315 329 Redbed
58 127 Tan Sandy Clay w/ sandstone 329 333 Red Sand
127 161 Sand & Gravel w/ Tan Sandy Clay Strata 333 335 Redbed
161 227 Redbed 335 340 Anhydrite
227 247 Red Sand
247 252 Redbed
252 272 Red Sand
272 281 Redbed
281 286 Red Sand
286 292 Redbed
292 294 Red Sand
294 297 Redbed
297 304 Red Sand
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-4-98 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. KSA-600A This Water Well Record was completed on (mo/day/yr) 4-10-98
Under the business name of Cramer Drilling Co. Box 176 Beaver, KS by (signature) Kelly Cramer
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-6545. Send one to WATER WELL OWNER and retain one for your records.