1 LOCATION OF WATER WELL: Township Number Range Number MeAde 33 28 Distance and direction from nearest town or city street address of well if located within city? 945+ 34 E 2 WATER WELL OWNER: TE NN15 RR#, St. Address, Box # Board of Agriculture, Division of Water Resources Bex Application Number: City, State, ZIP Code Depth(s) Groundwater Encountered 1..... ft. 2.... ft. 2.... ft. 3..... AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL 1.05... ft. below land surface measured on mo/day/yr ...9.-9.0Pump test data: Well water was ... 150 ... ft. after 1.... hours pumping ... 10 gpm NW _ _ ₩ ₩ WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well **D**Domestic 6 Oil field water supply 9 Dewatering 3 Feedlot 12 Other (Specify below) 2 Irrigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yrs sample was sub-Water Well Disinfected? Yes mitted 5 TYPE OF BLANK CASING USED: 5 Wrought iron CASING JOINTS: Glued. Clamped. 8 Concrete tile 3 RMP (SR) 1 Steel 6 Asbestos-Cement 9 Other (specify below) 4 ABS 7 Fiberglass 5....in. to . 120.....ft., Diain. toft., Dia Casing height above land surface. . PVC 8 RMP (SR) TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement 3 Stainless steel 1 Steel 5 Fiberglass 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 8 Saw cut SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut SCREEN-PERFORATED INTERVALS: From..... 2 Cement grout Bentonite 6 GROUT MATERIAL: Neat cement What is the nearest source of possible contamination: 10 Livestock pens Abandoned water well 7 Pit privy 1 Septic tank 4 Lateral lines 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 9 Feedyard 3 Watertight sewer lines 6 Seepage pit 13 Insecticide storage Direction from well? < How many feet? 10 FROM то LITHOLOGIC LOG FROM PLUGGING INTERVALS 10 5" Eggle Paintic PUCIIZO SPRZI 10 200 AST @ 75°F ASTM DZZ41 Well Casing IC-OASTM F480-95 Sandy brown clay 135 al igravel // 2 Full 20 BLIO/ 3 Hastings NE 135 155 Sandy brown 155 160 0014 99197