


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Meade	N $\frac{1}{2}$ $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$	23	T 33 S	R 29 E <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?

10 miles SW of Meade, KS--

2 WATER WELL OWNER:	H-30 Drilling	Board of Agriculture, Division of Water Resources Application Number: 90 0070
RR#, St. Address, Box # :	251 N Water, #10	
City, State, ZIP Code :	Wichita, KS 67202	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 280 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 105 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 105 ft. below land surface measured on mo/day/yr 02-15-90
	Pump test data: Well water was 109 ft. after 1 hours pumping 100 gpm
	Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 1/2 in. to 280 ft., and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded	
Blank casing diameter 5 in. to 280 ft., Dia in. to ft., Dia in. to ft.	
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. 320	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 220 ft. to 280 ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 80 ft. to 280 ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other dirt
Grout Intervals: From 1 ft. to 20 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? Southeast	How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	58	Tan Sandy Clay			
58	78	Brown and White Clay			
78	104	Tan Sandy Clay			
104	117	Sand			
117	211	Blue Clay			
211	218	Tan Sandy Clay			
218	269	Sand and Gravel			
269	276	White Clay and Gravel			
276	280	Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-15-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 02-15-90 under the business name of Howard Drllg. Co. Box 806 Beaver, OK 73932 by (signature) Howard Drllg. Co.
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.