

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Meade	Fraction SW 1/4 SW 1/4 SE 1/4	Section number 21	Township number T 33 S R 30 E/W	Range number
2. Distance and direction from nearest town or city: 7 Miles S of Plains, Kansas Street address of well location if in city:			3. Owner of well: V.V. McVey R.R. or street: Kismet City, state, zip code: Kansas		
4. Locate with "X" in section below: <p>Sketch map: 500' East of the SW corner of the SE 1/4, Sec. 21, T33S, R30W, Meade Co., Kansas.</p>			6. Bore hole dia. 28 in. Completion date 10-9-76 Well depth 480 ft.		
5. Type and color of material			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
			9. Casing: Material St 1 Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP 168 PVC <input type="checkbox"/> Weight 37 lbs./ft. Dia. 1 1/2 in. to 180 ft. depth Wall thickness: inches or Dia. 1 1/2 in. to 180 ft. depth gage No. 219		
			10. Screen: Manufacturer's name Doerr Type Millslot, Louver 16" Slot/gauze 1/8" Length 300 Set between 180 ft. and 480 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 3.4 mm		
			11. Static water level: 178 ft. below land surface Date 8-26-76		
			12. Pumping level below land surfaces: 188 ft. after 2 hrs. pumping 1060 g.p.m. 192 ft. after 1 hrs. pumping 1471 g.p.m. Estimated maximum yield 3100 g.p.m.		
			13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
			14. Well head completion: Pitless adapter <input checked="" type="checkbox"/> 12 inches above grade		
			15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
			16. Nearest source of possible contamination: Unk ft. 0 Direction 0 Type 0 Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
			17. Pump: Not installed Manufacturer's name Layne & Bowler Model number 12KM HP 1000 Volts 1000 Length of drop pipe 260 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:			19. Remarks:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley			(Use a second sheet if needed)		
			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne-Western Co., Inc. 102 Business name Garden City, Kansas License No. 102 Address Garden City, Kansas Signed R. Vincent Date 10-9-76 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5