

1 LOCATION OF WATER WELL: County: Meade	Fraction 1/4 XC-NW 1/4 NW 1/4	Section Number 23	Township Number T 33 S	Range Number R 30 E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city? **Go East on Meade Lake Road to**

Caution Light then 1mi East 1mi South 1mi East to location.

2 WATER WELL OWNER: Cities Service	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 3545 NW 58th	Application Number: PT-82 310
City, State, ZIP Code: Oklahoma City, Oklahoma 73112	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 340 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 153 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 187 ft. below land surface measured on mo/day/yr 6/3/82
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 60 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 in. to 340 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS	7 Fiberglass Threaded
Blank casing diameter 5 in. to 260 ft. Dia	in. to ft. Dia in. to ft.
Casing height above land surface 28 in. weight 2.78 lbs./ft. Wall thickness or gauge No. .256	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 260 ft. to 340 ft. From ft. to ft. From ft. to ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 160 ft. to 340 ft. From ft. to ft. From ft. to ft. From ft. to ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well	15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? Northeast of water well. How many feet? 100'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	surface			
2	23	clay			
23	45	caliche			
45	84	sandy clay			
84	158	medium to large sand			
158	200	fine sand			
200	245	medium to large sand			
245	268	sandy clay			
268	330	fine sand			
330	340	sandy clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 3, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) June 4, 1982 under the business name of Carlile Water Well Service by (signature) Edward E. Means
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

33

R

30

ED

SEC.

23

C

1/4

NW 1/4

NW 1/4

1/4