WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction			Section number		Township number Range number	
1. Location of well:	Seward	NE 1/4 SW 1/4 NW	1/4	16	5	T 33 S R 31 E/W	
2. Distance and direc	ction from nearest town or city:			er of well	_	rnest McVey	
12. Spenof Kismet Kansas					treet: te, zip code: Kismet, Kansas		
4. Locate with "X" in section below: Sketch map:					ode: P	78 10=0=76	
N		overen map.				6. Bore hole dia. 374 ft. Completion date	
			_		1	7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary	
l' i		the SW corner T33S, R3lW, Se				8. Use: Domestic Public supply Industry	
× × i		1990, ROIM, DE	Walu		, 112	Irrigation Air conditioning Stock	
					Lawn Oil field water Other 9. Casing: Material St1 Height: Above or below		
					7. Casing: Material Statistics Height: Above or below Threaded Welded X Surface 12 in.		
S						RMPPVCWeightlbs./ft.	
5. Type and color of material				From	То	Dia. 16 n. to 194, depth Wall Thickness; inches or Dia. in. to ft. depth gage No. 219	
/ [10. Screen: Manufacturer's name Foster, Doerr	
Top soil				0	7	Millslot, louver Type 1/8" Dia. 16" Slot/gauze 1/8" Length 180'	
Tan and white clay sand streaks				7	90	Slot/gauze 1/8" Length 180' Set between 194 ft. and 374 ft.	
Fine to coarse sand clay streaks				90	174	ft. andft.	
The to coarse sand cray stream						Gravel pack? Size range of material 3mm	
Hard tan clay				174	182	11. Static water level: mo./day/yr. 190 ft. below land surface Date 8-25-76	
Fine to coarse sand hard streaks				182	374	12. Pumping level below land surfaces:	
Blue hard sandy clay				374	500	210 ft. after 1 hrs. pumping 1060g.p.m. 1791g.p.m.	
				†		Estimated maximum yieldg.p.m.	
				<u> </u>		13. Water sample submitted: mo./day/yr Yes No Date	
				ļ	<u></u>	14. Well head completion:	
						Pitless adapter Inches above grade	
						15. Well grouted? <u>yes</u> With: Neat cement <u>X</u> Bentonite Concrete Depth: From Off. to 10 ft.	
				1		Depth: From O ft. to 10 ft.	
				ļ	-	16. Nearest source of possible contamination: ft Direction Type	
						Well disinfected upon completion?	
						Manufacturer's name Layne & Bowler	
						Model number 12KM HP Volts	
				-		Length of drop pipe 280 ft. capacity 950g.p.m.	
						Submersible Turbine	
	(Use a second	sheet if needed)				Jet Reciprocating Other 6	
18. Elevation:	19. Remarks:					20. Water well contractor's certification:	
					This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Topography:						Layne-Western Co., Inc. 102	
Hill Slope						Business name Address Garden City, Kansas	
X Upland						Signed Authorized representative	
Valley	l					Authorized representative	

MI-1023

Form WWC-5