WATER V	WELL RECORD	Form WWC	C-5	Division of Wate	r Resources; App. No.	
	TON OF WATER WELL:	Fraction). (Section Number		Range Number
County:		SW1/4 NW1/4/		30	T 33 S	R 33 EW
	and direction from nearest town				Systems (decimal deg	rees, min. of 4 digits)
	within city? Liberal: N			Latitude:		
	n Rd 7 to Rd G .7 RWELLOWNER: Bet	n on Rd G .I E ryl Scranton		Longitude:		
1		O Harold Blvd.		Datum:		
	TID C 1	peral, KS 67905	1	Data Collection I	Mathod:	
3 LOCAT		OMPLETED WELL		ft.	vicinou.	
LOCAT	ION					
•	AN "X" IN Depth(s) Ground	water Encountered (1).	220	ft. (2)	ft. (3)	ft.
l .	ON BOX: WELL'S STATION	C WATER LEVEL2.2	20	below land surface	measured on mo/day	/yr.08-30-0
	N Pump tes	water Encountered (1). C WATER LEVEL2.2 t data: Well water was	4.10	ft. after	hours pumping	§Ø gpm
	Est. Yield 5.	l .gpm: Well water was		ft. after	hours pumping	gpm
		TO BE USED AS: 5 Put Feedlot 6 Oil fiel	d water su	uppiy 8 Air (mly 9 Dew	conditioning 11 injuratering 12 Ot	er (Specify below)
W		Industrial 7 Domes				
Was a chemical/bacteriological sample submitted to Department? Yes NoX; If yes, mo/day/yrs						
Sample was submitted						
	S					**
	F CASING USED: 5 Wro	ught Iron 8 Con	crete tile	CASINO	JOINTS: Glued	X Clamped
1 Stee		estos-Cement 9 Otho	er (specify	below)	Welded	
$\frac{2}{2}$	C 4 ABS 7 Fiber	rglass			Threaded	· · · · · · · · · · · · · · · · · · ·
Blank casing diameter 5 in. to 320 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., Weight 3706lbs./ft. Wall thickness or guage NoS DR. 21316						
TYPE OF S	CREEN OR PERFORATION M	IATERIAL:		ios./it. wan un	ckliess of guage 1105	D-16 · · · · · · · · · · · · · · · · · · ·
1 Steel 3 Stainless Steel 5 Fiberglass 7-VC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 aw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 320 ft. to 360 ft., From ft. to ft.						
From						
GRAVEL PACK INTERVALS: From 1.60 ft. to 360 ft., From ft. to ft.						
	F	rom ft. to		ft., From	ft. to	ft.
(CDOUT	MATERIAL (1)	2 C		1	hole plug	
Grout Interv	MATERIAL: 1 Neat cement	2 Cement grout 3 B	entonite (t to f	From	ft to ft
Grout Intervals: From						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify						
	ver lines 5 Cess poo	l 8 Sewage lagoon	11 Fuel ste	orage 14 Ab	andoned water well	below)
			12 Fertiliz		l well/gas well	
	om well?					
		OGIC LOG	FROM	ТО	PLUGGING INT	ERVALS
0	1 Surface					
1	59 Sandy clay					
59 73 1	73 Sand 54 Clay			-		
	88 Sand and clay	ctroake				
	251 Sand Course					
	265 Sand and clay					
	350 Sand course					
	360 Sand and clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged						
under my jurisdiction and was completed on (mo/day/year) . 8						
under the business name of Howard Drilling Box 806 Beavbyr(signature) 3932						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline of orcic the correct answers. Send top						
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone						
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.						