WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| (4) | County | Fraction | | Section | number | Township number Range number |
|----------------------------------|--|---------------------------|------|------------|--|--|
| 1. Location of well: | Co. mr. 3-3 | SW 1/4 NE 1/4 NE | 1/4 | : | 1.4 | T 33 S R 33 E/W |
| 2. Distance and direc | Sewarda ction from nearest town or city: 10 | | | er of well | | Jayhawker Farms |
| | | | | | | .010 West Wall |
| | | | | | fidland, Texas | |
| 4. Locate with "X" i | | Sketch map: | | | | 6. Bore hole dia. 28 in. Completion date |
| N | | | | | | Well depth 422 ft. 6/19/76 |
| | | | | | | 7 Cable tool Rotary Driven Dug |
| D23M County Kanaga | | | | | Hollow rod Jetted Bored X_ Reverse rotary | |
| * W | | | | | 8. Use: Domestic Public supply Industry X_ Irrigation Air conditioning Stock | |
| 7 1 1 1 | | | | | Lawn Oil field water Other | |
| SW SE | | | | | | 9. Casing: Material <u>stl</u> Height: <u>Above</u> or below |
| <u> </u> | | | | | | Threaded Welded is- RMP PVC Weight 37lbs./ft. |
| S 1 → 1 Mile → 1 | | | | | Dia. 16 in. to 182ft. depth! Wall Thickness: inches or | |
| 5. Type and color of | | | | From | То | Dia in. to ft. depth gage No219 |
| | | | | | | 10. Screen: Manufacturer's name Doerr, Foster |
| Fine to c | oarse sand | | | 0 | 48 | Typelouver millslot 16" |
| | | | | | | Slot/gauze 1/811 Length 2401 |
| Tan &lay | | | | 48 | 68 | Set betweenft. andft. |
| Fine to coarse sand clay streaks | | | | 68 | 142 | ft. andft. Gravel pack? Ves Size range of material 4.4mm |
| | _ | | | 1.40 | 066 | |
| Fine to c | oarse sand | | | 142 | 266 | 11. Static water level: mo./day/yr. 151 ft. below land surface Date 5/5/76 |
| Tan sandy clay | | | | 266 | 310 | 12. Pumping level below land surfaces: 164 ft. after hrs. pumping 1080 g.p.m. |
| • | | | | | | 171 c. c. 1 1 1982 |
| Fine to coarse sand clay streaks | | | | 310 | 422 | Estimated maximum yield 3000 g.p.m. |
| Tan sandy clay | | | | 422 | 480 | |
| - | - | | | | | Yes X No Date |
| | | | | | | 14. Well head completion: Pitless adapter Inches above grade |
| | | | | | | 15. Well grouted? Ves |
| | | | | | | With: Neat cement Bentonite Concrete |
| | | | | | | Depth: From O ft. to 10 ft. |
| | | | | | | 16. Nearest source of possible contamination: unk ft Direction Type |
| | | | | | | Well disinfected upon completion? Yes No |
| | | | | | | 17. Pump: Not installed |
| | | | ···· | | | Manufacturer's name <u>Layne & Bowler</u> Model number <u>12 KL</u> HP <u>100</u> Volts <u>460</u> |
| | | | | | | Length of drop pipe 260 ft. capacity 900 g.p.m. |
| | | | | | | Туре: |
| | | | | | | Submersible Turbine Reciprocating |
| (Use a second sheet if needed) | | | | | | Centrifugal Other 6 |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's certification: |
| | | | | | | This well was drilled under my jurisdiction and this report |
| Topography: | | | | | | is true to the best of my knowledge and belief. Layne—Western Co., Inc. 102 |
| HIII | | | | | | Business name License No. |
| Slope | | | | | | Address Garden City Kansas |
| Upland Valley | | | | | | Signed Authorized representative Date 7/ |
| | | *** III | | | | 10010 |
| rward the white, blu | e and pink copies to the Department | of Health and Environment | | | | Form WWC-5 |