USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction	Section	number	Township number	Range number	
1. Location of well:	Seward	SW 1/4 NE 1/4 NE 1/4		2.3	T 33 S	R 33 E/ <u>W</u>	
2. Distance and direction from nearest town or city: 9 N, 2 3/4 E, 3. Owner of well: Steve E						-	
1/2 S. Liberal Kansas R.R. or Street address of well location if in city:				JIZ NOI EN BREIMON			
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia. 28 in. Completion date 2-7-77			7
4. Locate with "A" in section below: N					Well depth 420 ft.	- Comprehended date	
				[7 Cable tool Rotary	,	
Pivot point of the NE ₄ , Se						Bored X Reverse rotary	
T33S, R33W, Seward County,				isus.	8. Use: Domestic Public supply Industry		
{1						il field water Other	
SW SE I					9. Casing: MaterialST		
<u>†</u> <u> </u>					Threaded Welded Surface in . RMP PVC Weight 37 lbs ./ft .		
1 Mile					Dia. 16 in. to 179 ft. depth Wall Thickness: inches or		
5. Type and color of material			From	То	Diain. to ft. dept		,
				<u> </u>		Doerr, Foster	•
Fine to coarse sand				48	Typelouvered, m. Slot/gauze 1/811	iblslot 16''	
Tan clay			48	80	Set between 179		
			00	120	ft. a		
Fine to coarse sand, fine to med. gravel			80	130	11. Static water level:	mo./day/yr.	
Tan clay			130	140	150 ft. below land sur	face Date 5-12-76	
Fine to coarse sand fine to med. gravel			140	260	12. Pumping level below land surfaces: 165 ft. after 2 hrs. pumping 1060g.p.m. 180 ft. after 1 hrs. pumping 2012g.p.m.		
_			060	070			
Tan clay			260	270	Estimated maximum yield 2500 g.p.m.		
Fine to coarse sand, fine gravel				420]		
Fine to coarse sand dirty			420	472	Yes X No	Date	
			470	500	Pitless adapter	XX Inches above grade	
Red bed			472	500	15. Well grouted? X	Comments	ľ.
					Depth: From ft. to .	Bentonite Concrete Concrete	٠ <u>۲</u>
					16. Nearest source of possible	e contamination: unk	M
					ft Direction Well disinfected upon comple		
			+		17. Pump:	Not installed	ᢩᢩᠺ
						yne & Bowler ^ _ HP 100 Volts 460	N
						ft. capacity 900 g.p.m.	(₹)~
			1		Туре:	, , , , ,	U
<u> </u>			+	\vdash	Submersible Jet	X Turbine Reciprocating	0
(Use a second sheet if needed)					Centrifugal	Other O	ر ار
18. Elevation: 19. Remarks:					20. Water well contractor's o		M
					This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Topography:					Layne-Wester	n Co., Inc. 1022	ો્ટ
Hill Slope					Business name Address Garde	n City, Ks.	212
X Upland					Signed 72	Let Date	ا ہے۔ ا
Valley					Authorized rep	resentative 14 Feb 77	512
Forward the white, blu	ue and pink copies to the Department	of Health and Environment				Form WWC-5	W