


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Seward	Township name	Fraction NE, SW, SW	Section number 23	Town number 33S	Range number 33W
Distance and direction from nearest town or city: 7 Mi. N, 2 E, 1 1/4 Street address of well location if in city: N. 1/4 E of Liberal				3 Owner of well: Steve Burgess Address: 512 N. Sherman Liberal, Kansas		
Locate with "X" in section below: N 		Sketch map: Well drilled near center of SW 1/4, Sec. 23, T23S, R33W, Seward County, Ks.		4 Well depth: 383 ft. Date of completion 6-24-75 Well diameter 28 in.		
2 Type and color of material		From	To	5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
Sandy soil		0	2	6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well		
Fine sand		2	15	7 Casing: Material stl Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 37 lbs./ft. 16 in. to 383 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No in. to in. ft. depth		
Tan clay with fine sand		15	42	8 Screen: Manufacturer Foster & Doerr Type Mill slot & louver 16" Slot/gauze 1/8" Length 180 Set between 203 ft. and 383 ft. Fittings: 1.2mm - 9mm Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material		
Fine to coarse sand medium gravel		42	52	9 Static water level: 189 ft. below land surface Date 6-26-75		
Tan clay with limestone streaks		52	101	10 Pumping level below land surfaces: 205 ft. after 1/2 hrs. pumping 1100 g.p.m. 235 ft. after 1 hrs. pumping 2070 g.p.m. Estimated maximum yield 2500 g.p.m.		
Fine to coarse sand medium gravel		101	259	11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
Tan and green clay with sand & gravel		259	281	12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> Inches above grade		
Fine to coarse sand medium gravel		281	346	13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From 0 ft. to 10 ft.		
Tan clay		346	365	14 Nearest source of possible contamination: unk ft. Direction Type Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Fine to coarse sand medium gravel		365	383	15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Layne Model number 12K HP 100 Volts 480 Length of drop pipe 260 ft. capacity 800 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Tan & green clay		383	420	17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne-Western Co. Inc. 150 Business name License No. Address Box 686, Garden City, KS Signed [Signature] Date 2 Jul 75 Authorized representative		
16 Remarks: elevation Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5