

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 2 Township Number T 33 S Range Number R 34 EW

Distance and direction from nearest town or city street address of well if located within city?
 From Liberal - 9 Miles North, 3 Miles West, 4310 Ft. North & 100 Ft. West of SE Corner of section

2 WATER WELL OWNER: Bobby J. McBride
 RR#, St. Address, Box # : 601 E. 11th St. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hugoton, Kansas 67951 Application Number: 24267

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the NE quadrant. A vertical scale bar on the left is labeled '1 Mile'. The grid is labeled with N, S, W, E directions.]

4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION: 8-8-89 ft.
 Depth(s) Groundwater Encountered 1. 200 ft. 2. 300 ft. 3. ft.
 WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr 8-8-89
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 30 in. to 300 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 16 in. to 215 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. .250
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 215 ft. to 300 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 300 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? North How many feet? 590

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-8-89 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 9-15-89
 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

DIVISION OF ENVIRONMENT

SEP 20 1989

RECEIVED

0	1	Top soil
1	14	Fine sand
14	63	Brown sandy clay
63	119	Fine to medium sand - loose
117	138	Brown sandy clay
138	185	Fine to medium sand & gravel - loose
185	253	Fine to medium sand & gravel - few small clay streaks - loose
253	263	Brown sandy clay
263	293	Fine to medium sand & gravel - 10% clay - loose
293	305	Brown sandy clay - sticky
305	380	Brown sandy clay - blue streak of clay mixed

Test #2

Static Water Level - 200'

Location: NE 2-33-34

Bobby McBride
Seward
7-2-89

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Professional
MINTER-WILSON DRILLING CO
 INCORPORATED
 Irrigation
 and Domestic
 Water Systems
 Complete Installation
 and Repairing