


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NW 1/4 Section Number 21 Township Number T 33 S Range Number R 34 **EW**

Distance and direction from nearest town or city street address of well if located within city?
 FROM LIBERAL 9N 6W TO HUGOTON 1/2 S & E INTO LOC.

2 WATER WELL OWNER: PETE TULS
 RR#, St. Address, Box # : Hugoton, KS Board of Agriculture, Division of Water Resources
 City, State, ZIP Code Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL... 500 ft. ELEVATION: ...
 Depth(s) Groundwater Encountered 1. 120 ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL ... 120 ft. below land surface measured on mo/day/yr 2-4-94
 Pump test data: Well water was 140 ft. after 1 hours pumping 150 gpm
 Est. Yield ... 150 gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter ... 11 in. to ... 500 ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Dairy Farm
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter ... 6 in. to ... 500 ft., Dia ... in. to ... ft., Dia ... in. to ... ft.
 Casing height above land surface ... 24 in., weight ... 2.902 lbs./ft. Wall thickness or gauge No. ... 316
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From ... 400 ft. to ... 500 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From ... 240 ft. to ... 500 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ... HOLE PLUG
 Grout Intervals: From ... 1 ft. to ... 20 ft., From ... ft. to ... ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP			
2	26	SANDY CLAY			
26	50	SAND			
50	96	CLAY			
96	173	SANDY CLAY			
173	220	SAND			
220	300	SAND W/ CLAY STREAKS			
300	352	SAND			
352	375	CLAY			
375	380	SAND W/ CLAY STREAKS			
380	480	SAND			
480	500	BROWN CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-4-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWCL-430 This Water Well Record was completed on (mo/day/year) 2-4-94 under the business name of HOWARD DRIG. CO. BOX 806 BEAVER, OK 73932 by signature *Howard Drig*

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4