


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NW 1/4 Section Number 28 Township Number T 33 S Range Number R 34 **EW**

Distance and direction from nearest town or city street address of well if located within city?

51-83 NORTH OF LIBERAL 6 WEST, 1/2 SOUTH EAST INTO LOC.

2 WATER WELL OWNER: TULS DAIRY (PETE TULS) #2 WELL
 RR#, St. Address, Box # : *Shupston, KS* Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : *Shupston, KS* ✓ Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 500 ft. ELEVATION: ...
 Depth(s) Groundwater Encountered 1. 160 ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL: 180 ft. below land surface measured on mo/day/yr 3-11-94
 Pump test data: Well water was 200 ft. after 1 hours pumping 190 gpm
 Est. Yield 190 gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: 11 in. to 500 ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Dairy
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes... No... **X** ...; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued **X** Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 6 in. to 500 ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft.
 Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 316 SDR 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 400 ft. to 500 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 200 ft. to 500 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG
 Grout Intervals: From 1 ft. to 20 ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	55	SAND	490	494	SAND STONE
55	92	CLAY	494	500	CLAY
92	104	SANDY CLAY			
104	160	CLAY			
160	176	SAND			
176	184	CLAY			
184	220	SAND			
220	264	SANDY CLAY			
264	278	CLAY			
278	320	SANDY CLAY			
320	357	SAND			
357	380	CLAY			
380	465	SAND			
465	480	SANDY CLAY			
480	490	SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-11-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/year) 3-11-94 under the business name of HOWARD DRIG.CO.BOX 806 BEAVER, OK 73932 by (signature) *Oliver Howard*

OFFICE USE ONLY
T
R
EW
SEC.