

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STEVENS	SW ¼ SW ¼ NE ¼	20	T 33 S	R 35 EW

Distance and direction from nearest town or city street address of well if located within city?
 15 MILES EAST OF HUGOTON, KANSAS.

2 WATER WELL OWNER: DARRELL SKINNER
 RR#, St. Address, Box #: ROUTE 1, BOX 74
 City, State, ZIP Code: HUGOTON, KS 67951
 Board of Agriculture, Division of Water Resources
 Application Number: 40,416

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 665 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 300 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 26 in. to 665 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No..X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded X
2 PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter: 16 in. to 665 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	7 PVC	10 Asbestos-cement
2 Louvered shutter	4 Key punched	8 Saw cut	11 None (open hole)
		9 Drilled holes	
		10 Other (specify)	

SCREEN-PERFORATED INTERVALS:

From PERF. 300 ft. to 420 ft.	From SCREEN 420 ft. to 460 ft.
From PERF. 460 ft. to 540 ft.	From SCREEN 540 ft. to 580 ft.
From PERF. 580 ft. to 600 ft.	From SCREEN 600 ft. to 660 ft.

GRAVEL PACK INTERVALS:

From 20 ft. to 665 ft.	From PERF. 580 ft. to 600 ft.
	From SCREEN 600 ft. to 660 ft.

6 GROUT MATERIAL:

1 Neat cement	2 Cement grout	3 Bentonite	4 Other
---------------	----------------	-------------	---------

Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	CROPLAND-NOTHING

Direction from well? How many feet? IMMEDIATE VICINITY

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	240	SURFACE SAND & CLAY			
240	320	FINE TO MED. SAND W/SCATTERED CLAY STREAKS			
320	360	SANDY CLAY & FINE TO MED. COARSE SAND			
360	640	FINE TO MED. SAND			
640	660	COARSE SAND W/BROWN & SANDY CLAY			
660	670	RED CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/28/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 11/22/93 under the business name of KIM DRILLING, INC. by (signature) Darrell Skinner

OFFICE USE ONLY
T
R
EW
SEC.

00000