WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County | unty Fraction | | Section number | | Township number | Range number | | |
|---|--------------------------------------|---------------------------|-----|----------------|--|--|-----------------------------|--------------------|--|
| The Education of Well. | STerens | SE 1/4 NW 1/4 SW | 1/4 | , | | | R 34 | E/W | |
| 1人 カー ラグ・/ | | | | | | er of well: Larry Lichtcap | | | |
| Street address of well location if in city: | | | | | | | | 13051 | |
| 4. Locate with "X" in section below: Ske(gh map: | | | | | 6. Bore hole dia. 10 in. Completion date 2-2 | | | 2-20-76 | |
| N SAEGITING. | | | | | | Well depth 288 ft. | | | |
| <u> </u> | ! | | | | | 7 Cable tool _X Rotary | Driven Dug | | |
| | | | | | | Hollow rod Jetted Bored Reverse rotary | | | |
| ₩ | | | | | | 8. Use: Domestic Public supply Industry Irrigation Air conditioningX Stock | | | |
| = | | | | | | Lawn Oil field water Other | | | |
| | | | | | | 9. Casing: Material Height: Above or below | | | |
| | | | | | | ThreadedWeldedISurface/2in. | | | |
| S 1 ———— 1 Mile ———————————————————————————————————— | | | | | | RMPPVC_XWeight_3-24_lbs./ft. Dia. 5_in. to 288 ft. depth Wall Thickness: inches or | | | |
| 5. Type and color of material | | | | | То | Dia in. to ft. depth gage No. 253 | | | |
| | | | | | | 10. Screen: Manufacturer's name Pumpes | | | |
| topsain | light totan | to relish of | it | 0 | 40 | Type Polyrinal | Dia5 | , | |
| | | | | | 7.4 | Slot/gauze 1/8 Length 20' | | | |
| fine Sand lan & which | | | | 40 | 60 | Set between <u>268</u> ft. and <u>288</u> ft. | | | |
| Carse | sand brown | | | 60 | 80 | | ange of material <u>1/4</u> | - 1/4 | |
| 1 | | W Since Gra | / | 80 | 132 | 11. Static water level: | | ./day/yr. | |
| Couse sand (Sine Grarel | | | | | <u> </u> | ft. below land su | | 0-76 | |
| Calichie hard " Grare! | | | | 132 | 160 | 12. Pumping level below land surfaces: 15.5 ft. after 2 hrs. pumping 24 g.p.m. | | | |
| Sand prown Some Clare interded | | | | 160 | 1811 | ft. after hrs. pumping g.p.m. | | | |
| Mana prision Some Clays Concidera | | | | | | Estimated maximum yieldg.p.m. | | | |
| Sand fine to come / Some Clays | | | | 184 | 220 | 13. Water sample submitted: mo./day/yr. Yes X No Date | | | |
| Sand corse Clay halls Tight | | | | 220 | 240 | 14. Well head completion: | | | |
| Cia | | | | | | Pitless adapter | | | |
| Clay | | | | 240 | 254 | 15. Well grouted? | | | |
| Sand conse | | | | 256 | 260 | With: Neat cement Bentonite Concrete Depth: From 3 ft. to 3 ft. | | | |
| Clay | | | | 260 | 2/11 | 16. Nearest source of possible contamination: | | | |
| | | | | 100 | 264 | ft Direction Type | | | |
| Sand Corse | | | | 264 | 288 | Well disinfected upon completion? Yes No | | | |
| Falsed beds some Gravel | | | | 288 | 300 | 17. Pump: Not installed | | | |
| | and the second | <u> </u> | | | 1,,,,,, | Model number 19018 P | | olts 234/ | |
| | | | | + | - | Length of drop pipe | ft. capacity 2 | ±g.p.m. €)m | |
| | | | | | | Submersible | Turbir | ne l | |
| | // lan a as a a d | hant if monded) | | | | Jet | Recip | ocating | |
| 18. Elevation: | (Use a second s | neer it needed) | | | L | Centrifugal 20. Water well contractor's | | | |
| 10. Elevation: | 17. Remarks: | | | | | This well was drilled under | | is report | |
| T | | | | | | is true to the best of my kno | | -14 | |
| Topography: | | | | | | Slocem Dr Business name | 11/1 nG | 127 cense No. | |
| Slope | | | | | | Address Hugaton Kansas | | | |
| Upland | | | | | | Signed Authorized r | SCOTUM Date | . 3 -4 = 76 | |
| Valley | | | | | | Authorized re | · | | |
| Forward the white, blu | ue and pink copies to the Department | of Health and Environment | | | | | Form W | wc-s & | |