LOCATION OF WATER WELL:	Fraction	Fraction Form W			Section Number   Township Number			nher
LOCATION OF WATER WELL: County:	NW 1/4	NW 1/4	SE 1/4	٠		mber } S	Range Nun	EW.
Distance and direction from nearest town 700 Main, Hux	or city street addre	/4				, 0	3/	
WATER WELL OWNER:					***************************************	,		
R#, St. Address, Box #Taylor Foo	od Mart #621	7 Attn:	Anthony	Hall	Board of A	ariculture. (	Division of Water	Resourc
ity, State, ZIP Code P.O. Box	^ ^ ^ · · · · · · · · · · · · · · · · ·				Application Number:			
LOCATE WELL'S LOCATION WITH 4								
AN "X" IN SECTION BOX:	enth(s) Groundwate	er Encountere	d 1 8/.	<b>5</b> ft. 2		ft 3		ft
	VELL'S STATIC WA	ATER LEVEL	81.0	tt. below land surf	ace measured on	mo/day/vr	3-19-	77
				. ===== ft. af			-	-
NW  NE    <sub>E</sub>				ft. af				
1 ! 1 ' 1 1 -				ft., a		•		
. w	VELL WATER TO E				8 Air conditioning		Injection well	
	1 Domestic	3 Feedlot		117			•	low)
SW  SE	2 Irrigation	4 Industria	1 7 Lawn	ld water supply and garden only	0 Monitoring well	m	1W3	
	•			to Department? Ye				
	nitted	<b>J</b>	•		er Well Disinfecte			X
TYPE OF BLANK CASING USED:	5	Wrought iron	8 0		CASING JOI			d
1 Steel 3 RMP (SR)		Asbestos-Cer		Other (specify below		Weld		
(2)PVC 4 ABS	7	Fiberglass				Threa	aded	
lank casing diameter2 in	ı. to . 70	ft., Dia		in. to	ft., Dia		in. to .X	'
asing height above land surface YPE OF SCREEN OR PERFORATION	MATERIAL:		3CH 40	7 <b>)</b> PVC	10 Asb	estos-ceme	ent	
1 Steel 3 Stainless s		Fiberglass		8 RMP (SR)				
2 Brass 4 Galvanized	steel 6	Concrete tile		9 ABS	12 Nor	e used (op	en hole)	
CREEN OR PERFORATION OPENINGS	S ARE:	5	Gauzed wrapp	ped	8 Saw cut		11 None (open	hole)
1 Continuous slot (3)Mill	slot	6	Wire wrapped		9 Drilled holes			
_	punched	7	Torch cut	_	10 Other (specify	·) <i>.</i>		
CREEN-PERFORATED INTERVALS:	From	) ft.	to 4	ft. From	n	ft. t	o <del></del>	
em/D	From							
GRAVEL PACK INTERVALS:	From 69	ft.	to9.	ft., Fror	n <del>7.7.7.7.</del>	ft. t	o <del></del>	
	From	ft.	to	ft., Fror	n <b></b>	ft. t	0	
GROUT MATERIAL 1 Neat cer	ment , (2)0	Cement grout	3	Bentonite 4	Other			
Grout Intervals: From O ft.	. to <b>6.1</b>	.ft., From .	. 6.7	. ft. to <i>6.</i> 7.	ft., "From ::.		ft. to	
Vhat is the nearest source of possible co	ontamination:			10 Livest	ock pens	+4 A	bandoned <del>wate</del> r v	well
1 Septic tank 4 Lateral	4 Lateral lines		7 Pit privy		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess p	5 Cess pool		8 Sewage lagoon		12 Fertilizer storage (16)Other (specify I		other (specify belo	w)
3 Watertight sewer lines 6 Seepag	ge pit	9 Feedya	ard	13 Insect	ticide storage			
Direction from well?				How mar		Contam	inated Si	
FROM TO	LITHOLOGIC LO	G	FRO	ом то	Pl	UGGING I	NTERVALS	
GL 1.50 Concrete, 1	fill sand							
.50 21.50 Silty Clay								
50 31.00 Silty Sand	(SM)							
.00 69.00 Sand (SW)								
0.00 74.00 Silty Clay	(CL)							
.00 9\$.00   Sand (SP)								
.00 TD End of bore	hole							
					lyah Marma			
				1 1	lush Mount			
				Wa	aiver			
					Taylor			
CONTRACTOR'S OR LANDOWNER'S	S CERTIFICATION	: This water v	vell was (16 or	onstructed (9) reco	12/27/96 nstructed or 36 .	olugaed un	der my jurisdiction	n and w
ompleted on (mo/day/year) 3-1.	9-95				rd is true to the be			
Vater Well Contractor's License No	VC	This Wa	ater Well Reco	rd was completed		3-19-		
	PEI			by (signat	· <b>N</b> /1. /	A M	to Die	7
INSTRUCTIONS: Use typewriter or ball point per of Health and Environment, Bureau of Water, To	n. <u>PLEASE PRESS FIRM</u>			planks, underline or circle	the correct answers.			partment