T	WATER WELL R	ECOND FOIII	VVVVC-5	NOA 02a-				
LOCATION OF WATER WELL:	Fraction C 1/1	nic		Number	Township	<u>-</u>	Range Nu	mber 7 –
County: Stevens	SW/4 3 1/V	1/4 / 1/ 2		le	T 3	<u> う s</u>	R 3	
Distance and direction from nearest town or	1	,						
50005. 1	Main, H	ugoton,1	25 J					
WATER WELL OWNER: KASH	Qil (10.	MRSU) F Ka	neep	Wichita	15567	1212	
RR#, St. Address, Box # : 19915	E. Cedar	9090	rise k	amul	Board o	f Agriculture, D	ivision of Water	Resources
City, State, ZIP Code :	Liberal K	s <i>101901</i>		// W	Applicat	ion Number:		
LOCATE WELL'S LOCATION WITH 4	DEPTH OF COMPLETE	D WELL	10 f	ELEVAT	TION:			
	oth(s) Groundwater Enco		-					
	LL'S STATIC WATER L							
1								
NW NE	•	Well water was				•		
	. Yield gpm							
- W	e Hole Diameter	•	10					
≦	ILL WATER TO BE USE	D AS: 5 Pu	ıblic water su	pply	8 Air condition	-	njection well	
	1 Domestic 3 Fe		field water s	,	9 Dewatering		Other (Specify b	elow)
	2 Irrigation 4 In	dustrial 7 La	wn and gard	en only 1	0 Monitoring v	vell		
Wa:	s a chemical/bacteriolog	ical sample submi	tted to Depar	tment? Ye	sNo 🖈	; If yes,	mo/day/yr samp	le was sub-
S mitt	ted			Wat	er Well Disinfe	cted? Yes	No X	
TYPE OF BLANK CASING USED:	5 Wroug	ht iron	8 Concrete t	ile	CASING .	JOINTS: Glued	Clampe	ed
1 Steel 3 RMP (SR)	6 Asbest	os-Cement	9 Other (spe	cify below	1)	Welde	ed	
2 PVC_ 4 ABS	7 Fiberg				,	Threa	de <u>d.</u>	
Blank casing diameter	7 17 1	Dia	in to		ft Dia			
Casing height above land surface	_	t					1,-1	
TYPE OF SCREEN OR PERFORATION M.				103./1		Asbestos-ceme	- /	
			7 PVC	CD)				
1 Steel 3 Stainless ste	ū		8 RMP (5H)				
2 Brass 4 Galvanized s			9 ABS			None used (op-	,	1 -1-5
SCREEN OR PERFORATION OPENINGS		5 Gauzed wi			8 Saw cut		11 None (oper	n noie)
1 Continuous slot 3 Mill slo	ot	6 Wire wrap			9 Drilled hole	es		
2 Louvered shutter 4 Key p	ounched 70	7 Torch cut	00		10 Other (spe	cify)	<i></i>	
SCREEN-PERFORATED INTERVALS:	From	ft. to	.7 <i>0</i>	ft., Fron	n	ft. to) <i></i>	ft.
	From	ft. to	ح.مر	ft., Fron	n <i></i>	ft. to	o	
GRAVEL PACK INTERVALS:	From	ft. to	. 90	ft., Fron	n	ft. to	.	ft.
	From	ft. to		ft., Fron	n	ft. to		ft.
6 GROUT MATERIAL: 1 Neat ceme	ent 2 Cement	grout	3 Bentonite	14	Other			
Grout Intervals: From		From 2 .	to.	68	ft From		. ft. to	
What is the nearest source of possible con	•				ock pens		pandoned water	
1 Septic tank 4 Lateral lir		Pit privy		11 Fuel s	•		il well/Gas well	
2 Sewer lines 5 Cess poor		Sewage lagoon				40.0		low)
		• •			zer storage	Contor	ninated S	sito.
3 Watertight sewer lines 6 Seepage	pit 9	Feedyard			ticide storage	Cillur.	IM MICH	30 C
Direction from well?	ITHOUGHOUGH CO		EDOM T	How mar	ny feet?	PLUGGING II	ITEDVAL C	
	LITHOLOGIC LOG		FROM	ТО		FLOGGING II	VIERVALS	
0 5 gavel								
15 10 may								
10 24 Clay IW	SUME Sance							
24 45 Sama u	21Clay							
45 90 med to 0	Care Isana	Wickey						
d CNOIN								
, gaso								
	-	-						
	77.4							
		f						
CONTRACTOR'S OR LANDOWNER'S	CEDTIEICATION: This	water well was 14) construct	1 (2) ====	petruoted or f	3) plugged us	ter my juriedictic	on and was
CONTRACTOR'S OR LANDOWNER'S	19,000 this	water well was (1						
completed on (mo/day/year)	EEI						owledge and be	niei. Kansas
Water Well Contractor's License No.	100	his Water Well F	lecord was c			4-22	-6/10-1	
under the business name of WUU+	YCK YUMDY K	JAC INC		by (signat	ture) c	Jun (. WOO FEE	
INSTRUCTIONS: Use typewriter or ball point pen. of Health and Environment, Bureau of Water, Tope								epartment