

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: Stevens NE ¼ SW ¼ NE ¼ 16 T 33 S R 37 E/W

Distance and direction from nearest town or city street address of well if located within city?
300 S Monroe - Hugoton, KS

2 WATER WELL OWNER: Vet's Hall
 RR#, St. Address, Box # : 300 S Monroe Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hugoton, KS 67951 Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 150 ft. ELEVATION:

AN "X" IN SECTION BOX:

N			
--NW--			--NE--
		X	
--SW--			--SE--
W			E
S			

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 96.5 ft. below land surface measured on mo/day/yr 5-7-05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded X

Blank casing diameter 4 in. to 9.0 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 3 in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 1.50 ft. to 9.0 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 1.50 ft. to 87.2 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 87.2 ft. to 85.1 ft., From 85.1 ft. to 3.5 ft., From 3.5 ft. to 1.0 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Asphalt Parking

Direction from well? Immediate Vicinity How many feet? Lot

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	30	Clay	150	87.2	10/20 Sand
30	35	Fine sand	87.2	85.1	3/8 Bentonite Chips
35	95	Sand & clay mix	85.1	3.5	Bentonite grout
95	120	Sand with clay & caliche	3.5	1.0	Bentonite chips
120	150	Tan clay, caliche, & small gravel	1.0	0	Cement

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-5-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 665 This Water Well Record was completed on (mo/day/yr) 5-9-05 under the business name of Pratt Well Environmental by (signature) Steven E. Hill