

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stevens		SW 1/4 SW 1/4 NE 1/4	16	T 33 S	R 37 E/W
Distance and direction from nearest town or city street address of well if located within city? 500 S Main - Hugoton, KS					
2 WATER WELL OWNER: Maxine Ramey					
RR#, St. Address, Box # : 909 N Maize Rd, #212			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67212			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 150 ft. ELEVATION:			
<div style="text-align: center;">N - - NW - - - NE - - - - X - - W - - - E - - SW - - - SE - - S</div>		Depth(s) Groundwater Encountered 1 98.1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 98.1 ft. below land surface measured on mo/day/yr 5-7-05			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded Threaded X			
Blank casing diameter 4 in. to 9.0 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 3 in., weight lbs./ft. Wall thickness or gauge No. sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement					
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)					
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
		10 Other (specify) ft.			
SCREEN-PERFORATED INTERVALS: From 150 ft. to 90 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 150 ft. to 87.6 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 87.6 ft. to 85.5 ft., From 85.5 ft. to 2.5 ft., From 2.5 ft. to 1.0 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
		Driveway/Parking			
Direction from well? Immediate Vicinity How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	45	Clay	150	87.6	10/20 Sand
45	75	Sand, clay & some caliche	87.6	85.5	3/8 Bentonite Chips
75	150	Med & course sand, tan clay & caliche	85.5	2.5	Bentonite grout
			2.5	1.0	3/8 Bentonite Chips
			1.0	0	Cement
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 665 . This Water Well Record was completed on (mo/day/yr) 5-9-05 under the business name of Pratt Well Environmental by (signature) <i>Steven E. Pratt</i>					