

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sterens</u>		<u>SW 1/4 SW 1/4 NE 1/4</u>	<u>16</u>	T <u>33</u> S	R <u>37</u> E/W <u>①</u>
Distance and direction from nearest town or city street address of well if located within city? <u>Corner of 5th main, Hugoton, Ks</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>MRS. W. F. Ramsey</u> <u>909 maize Rd</u> <u>Sterens Co. Wichita, Ks 67211</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>89.31</u> 212 ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>84.94</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm. Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>90</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was sub- mitted			
		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded Threaded <u>X</u>			
2 PVC 4 ABS					
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No. <u>.154</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>70</u> ft. to <u>90</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>68</u> ft. to <u>90</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>0</u> ft. to <u>65</u> ft. From <u>65</u> ft. to <u>68</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		<u>contaminated site</u>			
Direction from well?		How many feet?			
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0	0.35	63	66	med sand w/ some limestone & gravel	
0.35	5	66	67	large gravel	
5	10	67	86	med sand, trace clay	
10	18	86	90	gravel	
18	20				
20	25				
25	30				
30	32				
32	35				
35	36				
36	40				
40	45				
45	46				
46	50				
50	63				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-17-97</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>554</u> This Water Well Record was completed on (mo/day/yr) <u>2-10-98</u>					
under the business name of <u>Wagner Pump & Well, Inc</u> by (signature) <u>Jay C. Wagner</u>					