

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stevens		NW 1/4 NW 1/4 NW 1/4	16	T 33 S	R 37 NW
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Stevens County Hwy Dept.					
RR#, St. Address, Box # : Hugoton, KS67051			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			MW # 7 Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 97.47 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 105 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No ☒			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded ☒			
		Blank casing diameter 2 in. to 65 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight 716 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 65 ft. to 105 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 63 ft. to 105 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 63 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Contaminated Site					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Silty Gravel			
2	10	Silty Clay			
10	12	Caliche			
12	15	Med. Brown Clay			
15	30	Sandy Clay			
30	35	Fine grained Sand			
35	50	Silty, Sandy Gravel			
50	58	Sandy Clay w/Caliche			
58	75	Med. Sand			
75	105	Traces of Caliche w/Sand Strks.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-21-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 9-19-97 under the business name of Woofter Pump & Well, Inc. by (signature) Gary L. Woofter					