USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

ᅷ	Щ.	-	5147	_		- //	- //		<u></u>
ı	- 1	ĸ	ΕW		sec	1/4	1/4	1/4	No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740

Form WWC-5

								T	opeka, Kansas 66620		
	County	Fraction		Section number			Town number	Range number			
1 Location of well:	STerens		NE 4 NE 4	VEY NEY SWY		15		T33 S	837 W		
Distance and directi	on from nearest town or cit	1: 1 E of HU	Goton	3 Owner	of well:	fwell: Mr. Bur cox and ringit cox					
Street address of we	Addre		HUGOTON KANSAS 17651								
Locate with "X" in section below: Sketch map:							4 Well depth: 220 ft. Date of completion 8-1-75 Well diameter 10 in.				
								Cable tool 🔀 Rotary [ Hollow rod 🗌 Jetted [	Driven Dug Bored Reverse rotary		
w				6 Use: Domestic Public supply Industry    Irrigation Air conditioning Commercial   Test well   Commercial							
	S S				7 Casing: Material Prc Height: above/below Threaded Welded Surface 12 in. Diam. Weight 2:24 lbs./ft. 1						
	—1 Mile→				in. to 5 ft. depth	Drive shoe? 🗌 Yes 🛛 No					
2	Тур	e and color of material			From	То	8	Screen: Saw S'	ict-		
si114	Gray				/	10		Manufacturer Pum P	<u>e v</u>		
Sand	fine	redish			10	40		Slot/gauzeL Set betweenft. and	ength		
Sand	4005	,	Some G	rarz/	40	85		Fittings: Gravel pack X Yes No	_		
Clay b	alls Conta	ning som		,	85	92		Static water level:  83 ft. below land surface			
Calichi		Limey	, J /	rarel	92	114		Pumping level below land sur	rfaces:		
Shale		Green Cas		İ	114	123		ft. after hrsft. after hrs Estimated maximum yield	. pumping g.p.m.		
calichi	= Soft	Calichia S	tringers	hard	123	146		Water sample submitted:			
Clay	shelf	bnown			146	160	-		re		
Clay ba	Ils prown	+ Sand fi	ne to c	orse	160	174		Pitless adapter Well grouted? X Yes	Inches above grade		
Clay shelf " some foint chy						197		Neat cement Benton Depth: From3 ft. to	ite Cement		
Clay be	ells Woorse				17 <u>6</u> 197	200	├──	Nearest source of possible of ft. 100 Direction Sc	ontamination:	Tank	
" "	/ cors	= sand b	rown		200	205		Well disinfected upon compl	etion? Yes No		
Sand		ine Grave	el pro	ėwn	205	220	15	Manufacturer's nameA	Not installed		
Clay	+ silt	Tan			220	240		Model number <u>SE 50-506</u> Length of drop pipe <u>168</u>			
ਦ								Type:  Submersible	Turbine		
	(use	a second sheet if needed	)					Jet Certrifugal	Reciprocating Other		
16 Remarks: elevat	tion						17	Water well contractor's certi			
Tonographii								report is true to the best of r	my knowledge and belief.		
Topography:								Slocum Well Business name	License No.	127	
Slope				Signed - Cara	um Date 8-20	-75					
Valley								Authorized repres	entative		