



1 LOCATION OF WATER WELL: County: Stevens		Fraction SW 1/4 NE 1/4 SE 1/4		Section Number 34	Township Number T 33 S	Range Number R 37 EW
Distance and direction from nearest town or city street address of well if located within city? 2 miles East of Hugoton 2 3/4 South						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Brubaker A-3 Gabbert & Jones 333 E. English Suite 215 Wichita, Ks. 67202 Board of Agriculture, Division of Water Resources Application Number: T87-529				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 280 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 150 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr 11-27-87 Pump test data: Well water was 120 ft. after 2 hours pumping 55 gpm Est. Yield 60 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 280 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 5 in. to 0-180 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)				
SCREEN-PERFORATED INTERVALS: From 130 ft. to 280 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 120 ft. to 280 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? Southwest How many feet? 250				
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG				
0	130	Overburden				
130	160	Clay				
160	180	Fine sand and clay				
180	200	Fine sand and clay				
200	220	Fine sand and clay				
220	240	Fine sand and clay				
240	260	Fine sand and clay				
260	280	Fine sand and clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-27-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 12/4/87 under the business name of T & W Water Well Service, Inc. by (signature) 						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4