

1 LOCATION OF WATER WELL: County: STEVEN'S		Fraction C 1/4 NW 1/4 SE 1/4		Section Number 4	Township Number T 33S S	Range Number R 38W EW																																																																																																
Distance and direction from nearest town or city street address of well if located within city? 6 MILES NORTHWEST OF HUGOTON, KS																																																																																																						
2 WATER WELL OWNER: GABBERT-JONES, INC. RR#, St. Address, Box # : 333 E ENGLISH, #215 City, State, ZIP Code : WICHITA, KS 67202					#1 PERRY "B" Board of Agriculture, Division of Water Resources Application Number: 930300																																																																																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"><p>1 Mile</p></div>		4 DEPTH OF COMPLETED WELL: 360 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 150 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 150 ft. below land surface measured on mo/day/yr 08-09-93 Pump test data: Well water was 285 ft. after 1 hours pumping 80 gpm Est. Yield 80 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 360 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																																																																				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 360 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 280 ft. to 360 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 260 ft. to 360 ft. From ft. to ft.																																																																																																						
6 GROUT MATERIAL: 1 Heat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG Grout Intervals: From 20 ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? EAST How many feet? 125																																																																																																						
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>3</td><td>BROWN CLAY</td><td></td><td></td><td></td></tr><tr><td>3</td><td>42</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>42</td><td>78</td><td>SANDY CLAY</td><td></td><td></td><td></td></tr><tr><td>78</td><td>112</td><td>SAND</td><td></td><td></td><td></td></tr><tr><td>112</td><td>142</td><td>JOINT CLAY</td><td></td><td></td><td></td></tr><tr><td>142</td><td>175</td><td>SANDY CLAY</td><td></td><td></td><td></td></tr><tr><td>175</td><td>184</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>184</td><td>192</td><td>SANDY CLAY</td><td></td><td></td><td></td></tr><tr><td>192</td><td>230</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>230</td><td>236</td><td>SAND</td><td></td><td></td><td></td></tr><tr><td>236</td><td>242</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>242</td><td>259</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>259</td><td>267</td><td>SAND</td><td></td><td></td><td></td></tr><tr><td>267</td><td>278</td><td>CLAY</td><td></td><td></td><td></td></tr><tr><td>278</td><td>360</td><td>SAND</td><td></td><td></td><td></td></tr></tbody></table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	3	BROWN CLAY				3	42	CLAY				42	78	SANDY CLAY				78	112	SAND				112	142	JOINT CLAY				142	175	SANDY CLAY				175	184	CLAY				184	192	SANDY CLAY				192	230	CLAY				230	236	SAND				236	242	CLAY				242	259	CLAY				259	267	SAND				267	278	CLAY				278	360	SAND			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																																	
0	3	BROWN CLAY																																																																																																				
3	42	CLAY																																																																																																				
42	78	SANDY CLAY																																																																																																				
78	112	SAND																																																																																																				
112	142	JOINT CLAY																																																																																																				
142	175	SANDY CLAY																																																																																																				
175	184	CLAY																																																																																																				
184	192	SANDY CLAY																																																																																																				
192	230	CLAY																																																																																																				
230	236	SAND																																																																																																				
236	242	CLAY																																																																																																				
242	259	CLAY																																																																																																				
259	267	SAND																																																																																																				
267	278	CLAY																																																																																																				
278	360	SAND																																																																																																				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-09-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 08-09-93 under the business name of HOWARD DRUG CO. BOX 806 BEAVER, OK 73932 by (signature) <i>Howard</i>																																																																																																						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																																						