WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | | | | | | 1 | | |
|--|--------|------------------|--|----|---|--|-------------------|-----------------|---|
| 1. Location of well: | County | Fraction | | | number | Township number | Range number | | |
| | | SE 1/4 SE 1/4 SE | | / | | 1 33 s | R 258 | E/W | |
| 2. Distance and direction from nearest town or city: H-LL set 3. Own | | | | | ner of well: STeren R. Paris | | | | |
| Street address of well location if in city: R.R. or state | | | | | street: R.R. tate, zip code: HuGoton Kansas 67951 | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | 1 | 6. Bore hole dia. 15 in. Completion date 1/1-74 | | | |
| | | | | | | Well depth 260ft. | | | |
| | | | | | | 7 Cable toolXRotary Driven Dug Hollow rod Jetted Bored Reverse rotary | | | |
| NW NE | | | | | | 8. Use: _X Domestic Public supply Industry | | | |
| | | | | | | Irrigation Air conditioning Stock | | | |
| SW SE | | | | | | LawnOil field waterOther 9. Casing: Material Height: Above or below Threaded Welded Surface24in. | | | |
| | | | | | | | | | S |
| 5. Type and color of material From To | | | | | | Dia. 5 in. to 260 ft. depth Wall Thickness: inches or | | | |
| 5. Type and color of material | | | | | То | Dia in. to ft. depth gage No: 250 10. Screen: Manufacturer's name \$\int loc \text{\texi}\text{\text{\text{\text{\texi}\text{\text{\texi{\texi{\texi{\texi{\texi{\texi{\texi{\texi{\texi}\texi{\texi{\texi{\texi} | | | |
| and sit sil | | | | | ч | | | | |
| you sell | | | | 0 | | Type Sak Color Dia. 5 Slot/gauze // Length 20 Set between 240 ft. and 260 ft. | | | |
| light tan silt | | | | н | ۶ | | | | |
| Clay cocoa collored stickey | | | | 8' | 20 | ft. andft. Gravel pack? X Size range of material 116 18 114 | | | |
| 9 | | | | 28 | 38 | 11. Static water level: mo./day/yr. | | | |
| Sand Coise brown | | | | | | ft. below land surface Date _//- 1 - 76 | | | |
| Clay Shelf Tan | | | | 38 | 42 | 12. Pumping level below land surfaces: 1/2 ft. after hrs. pumping | | | |
| Sand corse | | | | 42 | 50 | ft. after hrs. pumping g.p.m. | | | |
| 0.1:11 | | | | 50 | 50 | Estimated maximum yield 76al. Per ft. ar f. p.m. 13. Water sample submitted: mo./day/yr. | | | |
| Calichie Gerarel I Sand | | | | + | | Yes X No Date | | | |
| sand a/alay tan Ticht | | | | 80 | 90 | 14. Well head completion: | | | |
| Sand Corse 1 Grarz/ Corse | | | | | 260 | Pitless adapter 24 Inches above grade | | | |
| | | | | | | 15. Well grouted? Bentonite Concrete Depth: From ft. to ft. | | | |
| | | | | | | | | | |
| | | | | | | 16. Nearest source of possib | le contamination: | tel Pen | |
| | | | | | | Well disinfected upon comp | | No | |
| | | | | | 1 | 17. Pump: Manufacturer's name Flix | Not installed | | |
| | | | | | | Model number 10 BA 15 | HP V | olts <u>230</u> | |
| | | | | | | Length of drop pipe 140 | ft. capacity | 5_g.p.m. \ | |
| | | | | | | Type:X_ Submersible | Turbi | ne | |
| | | | | | | Jet Reciprocating | | | |
| (Use a second sheet if needed) | | | | | | Centrifugal | Other | * | |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report | | | |
| T | | | | | | is true to the best of my knowledge and belief. | | | |
| Topography: Hill | | | | | | Slocum Drilling 127 Business name License No. | | | |
| Slope | | | | | | Address Huseron Kansas | | | |
| | | | | | | Signed 1 auf St Authorized re | presentative /2 | 1-20-76 = | |
| | | | | | | 1, | | X | |