WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number | Range number |
|---|----------|------------------|-----|----------------|---|--|-------------------------------|
| 1. Location of well: | STerens | SE 1/4 SE 1/4 NE | 1/4 | 25 3 | | 1 33 S s | R 38 W E/W |
| 2. Distance and direction from nearest town or city: $2\omega / \frac{1}{2} = 3$. Owner of well: | | | | | | Kramer Profe | |
| Street address of well location if in city: HUGOTOM . Ka. R.R. or street: City, state, zip code: | | | | | | % A.E. Krame | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | by Bore hole dia. 10 in | . Completion date |
| N | | | | | Well depth 320 ft. | | |
| Round | | | | | | 7 Cable tool _X Rotary Hollow rod Jetted | |
| TOP | | | | | | 8. Use: X Domestic Public supply Industry | |
| | | | | | Irrigation Air conditioning Stock Lawn Oil field water Other | | |
| sw se X | | | | | 9. Casing: Material | Height: Above or below | |
| 130: Cattle Pens | | | | | 1 | Surface /8 in. | |
| S 1 Mile 1 | | | | | PVCWeightlbs./ft. Dia. 5 in. to 320 ft. depth Wall Thickness: inches or | | |
| 5. Type and color of | material | | ', | From | То | Dia in. to ft. dep | |
| <i>V i</i> - | 1,14 | | | | , | 10. Screen: Manufacturer's | |
| dark gray silty | | | | 0 | 6 | Slot/gauze /P | 1 |
| redish sand selly | | | | 4 | 14 | Set between300 | _ft. andft. |
| sand brown fine | | | | 14 | 82 | Gravel pack? Size ro | andft. |
| Clay halls Tan Gip while + sand brown | | | _ | 8 2 | 120 | 11. Static water level: | mo./day/yr. |
| | | | 71. | | | 12. Pumping level below land su | erface Date 3-30-76 |
| Sand brown corse some Claytjip | | | | 120 | 140 | 120 ft. after | hrs. pumping 13 g.p.m. |
| Sandstone Gray Thime stone + sand hard | | | | 140 | 150 | ft. after Estimated maximum yield | hrs. pumping g.p.m. |
| Clays blue Gray - tan - brown | | | | 150 | 157 | 13. Water sample submitted: | |
| Sand Conse brown | | | | 157 | 180 | Yes X No | Date |
| Sand Medium sine Some olay balls | | | | | | Pitless adapter | 18 inches above grade |
| Sand Medium sine / Some Clay Pall's | | | | 180 | 256 | 6. Well grouted?X | Rentonite X Concrete |
| Sand fine | | | | 200 | 230 | Depth: From ft. to | Bentonite Concrete |
| Clay silt balls - Gray - yellow - brown | | | | Ê | 290 | 16. Negrest source of possib | le contamination: |
| Sand Corse prown | | | | 290 | 270 | Well distillected open comp. | .,,,,, |
| | | | | | | 17. Pump: Manufacturer's name B | Not installed |
| | | | | | | Model number 1709P | HP Volts 236 |
| | | | | | | Length of drop pipe | ft. capacity <u>/3</u> g.p.m. |
| | | | | | | Submersible | Turbine |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Reciprocating Other |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's | |
| | | | | | This well was drilled under it is true to the best of my kno | my jurisdiction and this report weledge and belief. | |
| Topography: | | | | | | Slocom Dri | 11inG 127 |
| → Slope | | | | | | Business name HUGOTO | KA License No. |
| Upland Valley | | | | | | Signed Authorized re | presentative Date 8-4-76 |
| L Turiey | | | | | | | |